



## USB 1080P CAMERA SPECIFICATION

|                       |  |
|-----------------------|--|
| Model                 | AD-BHC7350U  |
| Max. Resolution       | Full HD 1920*1080  |
| Resolution & frame    | 320X240 QVGA MJPEG @60fps/ 352X288 CIF MJPEG @60fps<br>640X480 VGA MJPEG@60fps<br>1024X768 XGA MJPEG@30fps / 1280X720 HD MJPEG@30fps<br>1280X1024 SXGA MJPEG@30fps / 1920X1080 FHD MJPEG@30fps |
| Picture format        | MJPEG/ YUV2 (YUYV)   |
| Focus mode            | Manual focus   |
| Sensor                | 1/2.7" OV2735  |
| Mini illumination     | 0.05LUX  |
| Interface             | USB2.0 High Speed  |
| Lens                  | F3.6mm   |
| Support OTG           | USB2.0 OTG   |
| Support free driver   | USB Video Class (UVC)  |
| Size:                 | 41x41x41.5mm/100g  |
| Exposure              | Auto   |
| Auto white balance    | Auto   |
| AGC                   | Support  |
| Work temperature      | -20°C to 80°C  |
| Operating Humidity    | 30%~90%Rh  |
| Working power         | DC5V   |
| Cable                 | 1M   |
| Adjustable parameters | Brightness/Contrast/Color saturation /Definition/Gamma/WB  |
| Support OS            | WinXP/Vista/Win7/8/10 Wince with UVC/Linux/MAC-OS/Android  |
| Application area      | Entrance guard / high-speed capture / face recognition / advertising machine etc   |
| Certificate           | ROHS,CE,FCC  |