

MVC640 Microsoft Teams Rooms System

Microsoft Teams Rooms System for Medium Rooms

Yealink MVC640 is specially designed for Medium conference rooms. MVC640 includes third generation high-performance MINI-PC MCore Pro, touch panel MTouch E2, high-performance 4K PTZ camera UVC84, and Yealink speaker MSpeaker II. In this portfolio, you can choose different pickup microphone according to the needs of different conference rooms, DECT wireless microphone CPW65 and Wi-Fi wireless microphone VCM36-W. The surprise is that UVC84 in the portfolio has excellent performance. It has a 4K lens that supports 12x optical zoom and 3x digital zoom, an 80° wide Angle and a pan-tilt that allows it to cover every corner of the conference room. The Auto-framing function of UVC84 will free your mind, let you focus on the meeting without thinking about the picture of camera. With the Yealink camera plug-in controller, the camera can realize the preset position, one step adjustment, one step in place.



One Cable Technology



3-Microphone Array



Yealink Camera Control Plug-in



Auto Framing



Wireless Content Sharing and BYOD



Device Management



Key Features and Benefits

Native Microsoft Teams-tailored user interface, smooth conference experience

MTouch E2 has a built-in human motion sensor that allows it to automatically wake up conference system. Native Teams user interface, one click to start a meeting. Multi-function integrated design allows MTouch E2 to easily complete call control, camera control, content sharing and other functions.

Auto-framing

Yealink UVC84 camera allows for the auto-framing of all participants present at a meeting, freeing your hands and focusing on the meeting itself. Meanwhile, with the Yealink camera control plug-in and camera presets supported, the mechanical pan, tilt and zoom can be easily done quietly in one step. Empowered with 12x optical zoom, UVC84 supports 4K video calls that conduct business to capture everyone in the meeting room clearly.

Content sharing in real time

The unique wireless content sharing solution provides participants maximum flexibility, and a one-click content sharing can be simply realized by plugging into the WPP30. With a high resolution of 1080P/30 frames, it provides users with a better content sharing experience. Besides, the wired content sharing is also available by connecting to the USB-C or HDMI port.

Simple to deploy, easy to use

With the VCH port and USB port, Yealink audio and video system is specially designed for video meeting rooms so that the deployment can be easily extended. At the same time, with the cable management feature of Yealink MCore Pro, ensures the wire connection's stability, and the most appropriate deployment can be achieved according to the layout of the meeting room. One CAT5e is enough to connect the TV area and the conference table area and to complete the data transmission and power supply, no additional power supply or extension cable is needed, which not only simplifies the deployment but also effectively reduces deployment costs.

Manage your devices remotely

This solution supports Yealink Device Management Platform/Cloud Service, you can flawlessly manage, monitor, configure, update and diagnose all Yealink audio and video device peripherals on this platform remotely.


Specifications

Parameter	Description
Package Content	<ul style="list-style-type: none"> • MCore Pro, Gen-3 Mini-PC • MTouch E2, Gen-3 touch panel • UVC84 USB PTZ camera • CPW65 DECT wireless microphone(optional) • VCM36-W Wi-Fi wireless microphone (optional) • WPP30 wireless presentation pod
Preload	<ul style="list-style-type: none"> • Windows 10 IoT Enterprise X64 / Windows 11* IoT Enterprise X64 • Windows 10 IoT Enterprise License • Microsoft Teams Rooms App, support Skype for Business on-premise/online and Teams meetings • Yealink RoomConnect <p>*Windows 11 will be supported in 23H2</p>
MCore Pro, Gen-3 Mini-PC	<ul style="list-style-type: none"> • 11th Gen Intel® Core i5 • Memory: 8 GB (2 x 4GB) • Storage: 128 GB SSD • 3x HDMI video output with CEC supported • TPM2.0 • Kernel DMA • EDID • Wi-Fi: IEEE 802.11 a/b/g/n/ac/ax • Bluetooth: BT 5.2 • 1 x Yealink MTouch port (RJ45), connect to MTouch Plus/MTouch E2 • 4 x USB 3.0 Type-A • 1 x 10/100/1000M Ethernet port • 1 x Power port • 1 x Security lock slot, Integrated cable management
MTouch E2 touch panel	<ul style="list-style-type: none"> • 8-inch IPS screen • 1280 x 800 resolution • 10-point capacitive touch screen • 3.5 mm headset jack • Angle adjustable bracket (28° - 50°) • 1080P/30FPS FHD for sharing • Support wired and wireless content sharing • Built-in Wi-Fi AP for Yealink wireless presentation device • HDMI/USB-C HD video input

<p>UVC84 USB PTZ camera</p>	<ul style="list-style-type: none"> • 4K Sensor • 12x optical zoom • Field of view (diagonal): 80° • Auto Framing • Camera presets • Pan range: 200° • Tilt range: 130° • 1 x Line-out (3.5mm) • 1 x Yealink Microphone port (RJ-45) • 1 x USB 2.0 Type-B • 1 x Power port • 1 x Security lock slot • 1 x Reset slot
<p>VCM36-W(optional)</p>	<ul style="list-style-type: none"> • Built-in three-wheat matrix • 360° omnidirectional pickup • Signal to Noise ratio: 60dB SPL@1KHz,A-weighted • Loudest Pressure level: 115dB@1KHz, THD< 3% • Equivalent noise: -105dBFS(A) • Dynamic range: 81dBFS • Sensitivity: -45dB±2 • Frequency response: 100Hz-8KHz • 2-meter radius full duplex range • 6 m pickup radius • 2450mAh battery with wireless charging • 7 days standby time, up to 12 hours of continuous use • Two-color LED capacitive touch mute button
<p>CPW65</p>	<ul style="list-style-type: none"> • 360° omnidirectional pickup • Signal-to-noise ratio: 65dB SPL@1KHz,A-weighted • Loudest Pressure level: 110dB@1KHz, THD< 3% • Equivalent noise: -110dBFS(A) • Dynamic range: 81dBFS • Sensitivity: -32db+/-2 • Frequency response: 100Hz-8KHz • 2-meter radius full duplex range • 6 m pickup radius • Use Yealink WDD60 for pairing • Two-color LED capacitive touch mute button

<p>MSpeaker II</p>	<ul style="list-style-type: none"> • Frequency response: 106Hz-20 KHZ • Maximum Loud Pressure level: $88 \pm 3\text{dB}@8\text{W} / 1\text{M}$ • Sensitivity: $79 \pm 3\text{dB}@1\text{W}/1\text{M}$ • S/N: $\geq 70\text{dB}$ • 3.5mm linear input interface
<p>Package Features</p>	<ul style="list-style-type: none"> • N.W/CTN: 7.7 Kg • G.W/CTN: 8.4 Kg • Carton Meas: 595 mm x 393 mm x 258 mm

Scene Graph in a Conference Room



MVC Kit

Meeting Room Type	Model	Kit Contain
<p>Medium Meeting Room</p>	<p>MVC640-C4-F13</p>	<p>UVC84 CPW65 MSpeaker II MCore Pro MTouch E2 WDD60 WPP30</p>

[Click here](#) to go to the product introduction of the Yealink official website.