

Artikelnr.: 385847

EDS-208-M-ST - Unverwalteter Ethernet-Switch der Einstiegsklasse mit 7 10100BaseT(X)-Ports

ab **230,22 EUR**

Artikelnr.: 385847
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Moxa has a large portfolio of industrial unmanaged switches that have been specifically designed for industrial Ethernet infrastructure. Our unmanaged Ethernet switches uphold the stringent standards that are required for operational reliability in harsh environments. Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature. Ethernet Interface- 10/100BaseT(X) Ports (RJ45 connector) 7 Auto negotiation speed Full/Half duplex mode Auto MDI/MDI-X connection- 100BaseFX Ports (multi-mode ST connector) 1- Standards IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX IEEE 802.3x for flow control Switch Properties- MAC Table Size 2 K- Packet Buffer Size 768 kbits- Processing Type Store and Forward Power Parameters- Connection 1 removable 4-contact terminal block(s)- Input Current 0.11 A @ 24 VDC- Input Voltage 12/24/48 VDC Redundant dual inputs- Operating Voltage 9.6 to 60 VDC- Overload Current Protection Supported- Reverse Polarity Protection Supported DIP Switch Configuration- Ethernet Interface Broadcast storm protection Physical Characteristics- Housing Aluminum- IP Rating IP30- Dimensions 50 x 114 x 70 mm (1.96 x 4.49 x 2.76 in)- Weight 275 g (0.61 lb)- Installation DIN-rail mounting Wall mounting (with optional kit) Environmental Limits- Operating Temperature -10 to 60°C (14 to 140°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- Safety UL 508 EN 62368-1 (LVD)- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Hazardous Locations ATEX Class I Division 2- Railway EN 50121-4- Traffic Control NEMA TS2- Vibration IEC 60068-2-6- Shock IEC 60068-2-27- Freefall IEC 60068-2-31- Maritime ABS LRNKDNVMTBF- Time EDS-208A: 3,248,014 hrs EDS-208A-MM/SS: 2,705,157 hrs EDS-208A-M/S: 2,943,335 hrs- Standards Telcordia (Bellcore), GB

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

