

Artikelnr.: 385980

EDS-405A-MM-SC-T - Verwalteter Ethernet-Switch der Einstiegsklasse mit 3 10/100BaseT(X)-Ports

ab **596,16 EUR**

Artikelnr.: 385980
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Die verwalteten Layer-2-Switches von Moxa zeichnen sich durch industrietaugliche Zuverlässigkeit, Netzwerkredundanz und Sicherheitsfunktionen auf der Grundlage des IEC 62443-Standards aus. Wir bieten robuste, branchenspezifische Produkte mit mehreren Industriezertifizierungen, wie z. B. Teile der Norm EN 50155 für Bahnanwendungen, IEC 61850-3 für Energieautomatisierungssysteme und NEMA TS2 für intelligente Transportsysteme. Verwalteter Ethernet-Switch der Einstiegsklasse mit 3 10/100BaseT(X)-Ports, 2 100BaseFX-Multimode-Ports mit SC-Steckern, Betriebstemperatur -40 bis 75 °C Ethernet Interface- 10/100BaseT(X) Ports (RJ45 connector) 3 Auto negotiation speed Full/Half duplex mode Auto MDI/MDI-X connection- 100BaseFX Ports (multi-mode SC connector) 2- Optical Fiber Read more- Standards IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX IEEE 802.3x for flow control IEEE 802.1D-2004 for Spanning Tree Protocol IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1w for Rapid Spanning Tree Protocol Ethernet Software Features- Filter 802.1Q VLAN MRP GVRP IGMP v1/v2 Port-based VLAN- Industrial Protocols EtherNet/IP Modbus TCP- Management Back Pressure Flow Control BOOTP DHCP Option 66/67/82 DHCP Server/Client Flow control IPv4/IP v6 LLDP Port Mirror RARP RMON SMT PSNMP Inform SNMP v1/v2c/v3 Syslog Telnet TFTP- MIB Bridge MIB Ethernet-like MIB MIB-IIP-BRIDGE MIB RMON MIB Groups 1, 2, 3, 9 RSTP MIB- Redundancy Protocols RSTP STP Turbo Chain Turbo Ring v1/v2- Time Management NTP Server/Client SNTP Switch Properties- IGMP Groups 256- MAC Table Size 2 K- Max. No. of VLANs 64- Packet Buffer Size 1 Mbits- Priority Queues 4- VLAN ID Range VID 1 to 4094 Serial Interface- Console Port RS-232 (Tx, Rx, GND), 10-pin RJ45 (115200, n, 8, 1) DIP Switch Configuration- Ethernet Interface Turbo Ring, Master, Coupler, Reserve Input/Output Interface- Alarm Contact Channels Relay output with current carrying capacity of 1 A @ 24 VDC Power Parameters- Input Voltage 12/24/48 VDC Redundant dual inputs- Operating Voltage 9.6 to 60 VDC- Input Current 0.594 A @ 12 VDC 0.286 A @ 24 VDC 0.154 A @ 48 VDC- Overload Current Protection Supported- Reverse Polarity Protection Supported- Connection 1 removable 6-contact terminal block(s) Physical Characteristics- Housing Metal- IP Rating IP30- Dimensions 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)- Weight 650 g (1.44 lb)- Installation DIN-rail mounting Wall mounting (with optional kit) Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- Safety UL 508 UL 60950-1 EN 62368-1 EN 60950-1- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Hazardous Locations ATEX Class I Division 2- Railway EN 50121-4- Traffic Control NEMA TS2- Vibration IEC 60068-2-6- Shock IEC 60068-2-27- Freefall IEC 60068-2-31- Maritime DNV LR MTBF- Time 1,429,327 hrs- Standards Telcordia (Bellcore), GB

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

