

Artikelnr.: 385782

## VPOR 06-2L28M - EN 50155, 1080P Bild, kompakte IP Kamera mit M12 Stecker, 1 Audio Eingang, 24 V

ab **737,65 EUR**

Artikelnr.: 385782  
Versandgewicht: 0.50 kg  
Hersteller: MOXA



### Produktbeschreibung

Our selection of IP cameras includes dome, box, and cameras that have rugged designs. They comply with parts of the EN 50155 standard, enabling them to perform reliably and deliver superior image quality suitable for a range of applications. EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature

Memory- microSD Slot  
SDXC Input/Output Interface- Digital Input Channels 1- Digital Inputs+13 to +30 V for state 1-30 to +1 V for state 0  
Max. input current: 8 mA- Connector DB9 male  
Ethernet Interface- 10/100BaseT(X) Ports (M12 D-coded 4-pin female connector) 1  
Ethernet Software Features- Protocols TCP/IP IPv4/IPv6 UDP HTTP RTP/RTSP ARP UPnP PPTP FTP NTPT Client DNS QoS IGMP v3 ICMP SNMP v1/v2c/v3 DHCP Opt 66/67 HTTP SSIP Security Functions- Password User-level password protection- Filter IP address- Encryption HTTP SSSH Power Parameters- No. of Power Inputs 1- Input Voltage 12/24 VDC- Input Current 0.86 A @ 12 VDC, 0.35 A @ 24 VDC- Power Connector DB9 male  
Camera Characteristics- Sensor 1/3-in 1080P progressive scan CMOS- Lens f=2.8 mm, F2.0, Diagonal 94°, Horizontal 85°, Vertical 45°- Minimum Illumination Color: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec)- Synchronization Internal- White Balance ATW/AWB- Electronic Shutter Auto, Fixed (1/30 to 1/25000 sec)- S/N Ratio Maximum 50 dB (AGC off; DNR on)- DNR (digital noise reduction) Built-in 2D/3D DNR- WDR (wide dynamic range) 100 dB- AGC (auto gain control) 2X, 4X, 8X, 16X- Flickerless Control Automatic, 50 Hz, 60 Hz modes- Image Rotation Flip, Mirror, 90°, 180°, 270° rotation- Image Setting Manual tuning with saturation, sharpness, and contrast- Camera Angle Pan: ±15°, Tilt: 0° to 90° (controlled manually)  
Video Interface- Video Compression H.264 (ISO/IEC 14496-10) or MJPEG- Video Output via Ethernet- Video Streams 4 independent H.264 or MJPEG video streams- Video Viewing DynaStream™ support for changing the video frame rate automatically  
CBR Pro™ for good image quality in limited bandwidth transmissions  
3 privacy mask areas provided  
Adjustable image size and quality  
Timestamp and text overlay  
OSD (On Screen Display) position adjustable  
Maximum of 10 simultaneous unicast connections, 50 multicast clients  
Audio Interface- Audio Format Mono, PCM (G.711) AAC- Audio Inputs 1 x line-in, with DB9 male connector  
Camera Software Development- Video Standards ONVIF Profile S  
Camera Alarm Software Features- Intelligent Video Camera tampering detection- Video Motion Detection 3 independently configurable areas- Scheduling Daily repeat timing schedule- Imaging JPEG snapshots for pre/trigger/post alarm images- Custom Alarms HTTP event servers for setting customized alarm actions- FTP Messaging Automatic transfer of stored images via FTP as event-triggered actions- Pre-Alarm Buffer 50 MB video buffer for JPEG snapshot images- Video Recording Event recordings stored on the SD card  
Software Requirements- Memory Size 2 GB- Operating System Windows 7 or above- Browser Internet Explorer 9.x or above- Multimedia DirectX 9.0C or above  
Physical Characteristics- Housing IP66 rain and dust protection  
Metal housing, PC dome cover  
K8 vandal resistant protection- Dimensions 110 x 115.5 x 61.8 mm (4.33 x 4.53 x 2.43 in)- Weight 620 g (1.37 lb)- Installation Panel mounting- Protection PCB conformal coating is optional and provided on request. If conformal coating is required, please contact Moxa.  
Environmental Limits- Operating Temperature -25 to 55°C (-13 to 131°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)- Ingress Protection IEC 60529, IP66- Vandal Resistance EN 62262, IK8- Altitude 2000 m  
Standards and Certifications- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Freefall IEC 60068-2-31- Railway Fire Protection EN 45545-2- Safety UL 62368-1- Shock IEC 60068-2-27, IEC 61373, EN 50155- Vibration IEC 60068-2-64, IEC 61373, EN 50155- Railway EN 50155 (complies with a portion of EN 50155 specifications)  
MTBF- Time 1,063,089 hrs- Standards Telcordia SR332

### Technische Daten

Hier gehts zum Artikel  
Alle Informationen,  
tagesaktuelle Preise und  
Verfügbarkeiten

