

Artikelnr.: 385782

VPOR 06-2L28M - EN 50155, 1080P Bild, kompakte IP Kamera mit M12 Stecker, 1 Audio Eingang, 24 V

ab **695,76 EUR**

Artikelnr.: 385782
Versandgewicht: 0.50 kg
Hersteller: MOXA



Produktbeschreibung

Our selection of IP cameras includes dome, box, and cameras that have rugged designs. They comply with parts of the EN 50155 standard, enabling them to perform reliably and deliver superior image quality suitable for a range of applications. EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature

Memory- microSD Slot
SDXC Input/Output Interface- Digital Input Channels 1- Digital Inputs+13 to +30 V for state 1-30 to +1 V for state 0
Max. input current: 8 mA- Connector DB9 male
Ethernet Interface- 10/100BaseT(X) Ports (M12 D-coded 4-pin female connector) 1
Ethernet Software Features- ProtocolsTCP/IPIPv4/IPV6UDPHTTTPRTP/RTSPARPUPnPFTPTFTPNTPT ClientDNSQoSIGMP v3ICMPSNMPv1/v2c/v3DHCP Opt66/67HTTPSSIPSecurity Functions- Password User-level password protection- Filter IP address- EncryptionHTTPTSSSHPower Parameters- No. of Power Inputs 1- Input Voltage 12/24 VDC- Input Current 0.86 A @ 12 VDC, 0.35 A @ 24 VDC- Power Connector DB9 male
Camera Characteristics- Sensor 1/3-in 1080P progressive scan CMOS- Lens f=2.8 mm, F2.0, Diagonal 94°, Horizontal 85°, Vertical 45°- Minimum Illumination Color: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec)- Synchronization Internal- White Balance ATW/AWB- Electronic Shutter Auto, Fixed (1/30 to 1/25000 sec)- S/N Ratio Maximum 50 dB (AGC off; DNR on)- DNR (digital noise reduction) Built-in 2D/3D DNR- WDR (wide dynamic range) 100 dB- AGC (auto gain control) 2X, 4X, 8X, 16X- Flickerless Control Automatic, 50 Hz, 60 Hz modes- Image Rotation Flip, Mirror, 90°, 180°, 270° rotation- Image Setting Manual tuning with saturation, sharpness, and contrast- Camera Angle Pan: ±15°, Tilt: 0° to 90° (controlled manually)
Video Interface- Video Compression H.264 (ISO/IEC 14496-10) or MJPEG- Video Output via Ethernet- Video Streams 4 independent H.264 or MJPEG video streams- Video ViewingDynaStream™ support for changing the video frame rate automatically
CBR Pro™ for good image quality in limited bandwidth transmissions
3 privacy mask areas provided
Adjustable image size and quality
Timestamp and text overlay
OSD (On Screen Display) position adjustable
Maximum of 10 simultaneous unicast connections, 50 multicast clients
Audio Interface- Audio FormatMono, PCM (G.711)AAC- Audio Inputs 1 x line-in, with DB9 maleconnector
Camera Software Development- Video Standards ONVIF Profile SCamera Alarm Software Features- Intelligent Video Camera tampering detection- Video Motion Detection 3 independently configurable areas- Scheduling Daily repeat timing schedule- Imaging JPEG snapshots for pre/trigger/post alarm images- Custom Alarms HTTP event servers for setting customized alarm actions- FTP Messaging Automatic transfer of stored images via FTP as event-triggered actions- Pre-Alarm Buffer 50 MB video buffer for JPEG snapshot images- Video Recording Event recordings stored on the SD card
Software Requirements- Memory Size 2 GB- Operating System Windows 7 or above- Browser Internet Explorer 9.x or above- Multimedia DirectX 9.0C or above
Physical Characteristics- HousingIP66 rain and dust protectionMetal housing, PC dome coverIK8 vandal resistant protection- Dimensions 110 x 115.5 x 61.8 mm (4.33 x 4.53 x 2.43 in)- Weight 620 g (1.37 lb)- Installation Panel mounting- Protection PCB conformal coating is optional and provided on request. If conformal coating is required, please contact Moxa.
Environmental Limits- Operating Temperature -25 to 55°C (-13 to 131°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)- Ingress Protection IEC 60529, IP66- Vandal Resistance EN 62262, IK8- Altitude 2000 m
Standards and Certifications- EMI CISPR 32, FCC Part 15B Class A- EMSIEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/mIEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kVIEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kVIEC 61000-4-6 CS: 10 VIEC 61000-4-8 PFMF- Freefall IEC 60068-2-31- Railway Fire Protection EN 45545-2- Safety UL 62368-1- Shock IEC 60068-2-27, IEC 61373, EN 50155- Vibration IEC 60068-2-64, IEC 61373, EN 50155- Railway EN 50155 (complies with a portion of EN 50155 specifications)
MTBF- Time 1,063,089 hrs- Standards Telcordia SR332

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

