

Artikelnr.: 387971

EDS-2005-EL-T - Unverwalteter Fast-Ethernet-Switch mit 5 10/100BaseT(X)-Ports

ab **142,08 EUR**

Artikelnr.: 387971
Versandgewicht: 0.20 kg
Hersteller: MOXA



Produktbeschreibung

Moxa verfügt über ein großes Portfolio an industriellen unmanaged Switches, die speziell für industrielle Ethernet-Infrastrukturen entwickelt wurden. Unsere unverwalteten Ethernet-Switches erfüllen die strengen Standards, die für die Betriebszuverlässigkeit in rauen Umgebungen erforderlich sind. Ethernet Interface - 10/100BaseT(X) Ports (RJ45 connector): 5 Full/Half duplex mode Auto MDI/MDI-X connection Auto negotiation speed - Standards IEEE 802.3 for 10BaseT IEEE 802.1p for Class of Service IEEE 802.3u for 100BaseT(X) IEEE 802.3x for flow control Switch Properties - Processing Type: Store and Forward - MAC Table Size: 2 K - Packet Buffer Size: 768 kbits DIP Switch Configuration - Ethernet Interface: Quality of Service (QoS), Broadcast Storm Protection (BSP) Power Parameters - Connection: 1 removable 2-contact terminal block(s) - Input Current: 0.039 A @ 24 VDC - Input Voltage: 12/24/48 VDC - Operating Voltage: 9.6 to 60 VDC - Overload Current Protection: Supported - Reverse Polarity Protection: Supported Physical Characteristics - Dimensions: 18 x 81 x 65 mm (0.7 x 3.19 x 2.56 in) - Installation DIN-rail mounting Wall mounting (with optional kit) - Weight: 113.5 g (0.25 lb) - Housing: Metal Environmental Limits - Ambient Relative Humidity: 5 to 95% (non-condensing) - Operating Temperature EDS-2005-EL: -10 to 60°C (14 to 140°F) EDS-2005-EL-T: -40 to 75°C (-40 to 167°F) - Storage Temperature (package included): -40 to 85°C (-40 to 185°F) Standards and Certifications - Safety UL 61010-2-201 EN 62368-1 - EMC EN 55032/35 EN 61000-6-2/-6-4 - EMI: CISPR 22, 32, FCC Part 15B Class A - EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF - Shock: IEC 60068-2-27 - Vibration: IEC 60068-2-6 - Freefall: IEC 60068-2-32 MTBF - Time: 5,249,061 hrs - Standards: Telcordia (Bellcore), GB

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

