

Artikelnr.: 385897

VPOR T P06-1MP-M12-CAM42 - EN50155, HD, kompakte IP-Kamera, M12-Anschluss, 1 Audio-Eingang, PoE

ab **604,01 EUR**

Artikelnr.: 385897
Versandgewicht: 0.50 kg
Hersteller: MOXA



Produktbeschreibung

Unsere Auswahl an IP-Kameras umfasst Dome- und Box-Kameras sowie Kameras mit robustem Design. Sie erfüllen Teile der Norm EN 50155, sodass sie zuverlässig funktionieren und eine überragende Bildqualität liefern, die für eine Reihe von Anwendungen geeignet ist. Ethernet Interface - PoE Ports (10/100BaseT(X), M12 D-coded 4-pin female connector): 1 Ethernet Software Features - Protocols TCP/IPIPv4UDPHTTPTFTP/RTSPARPUPnPFTPTFTPNTPT ClientDNSQoSIGMP v3ICMPSNMPv1/v2c/v3DHCP Opt66/67HTTPS Security Functions - Password: User-level password protection - Filter: IP address - Encryption: HTTPS Power Parameters - No. of Power Inputs: 1 - Source of Input Power: PoE (IEEE 802.3af) - Input Current: 0.12 A @ 48 VDC Camera Characteristics - Sensor: 1/2.7-in HD progressive scan CMOS - Lens: f=4.2 mm, F1.8, Diagonal 87°, Horizontal 80°, Vertical 43° - Camera Angle: Pan: ±30°, Tilt: 0° to 90° (controlled manually) - Minimum Illumination: Color: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec) - Synchronization: Internal - White Balance: ATW/AWB - Electronic Shutter: Auto, Fixed (1/30 to 1/25000 sec) - S/N Ratio: Maximum 50 dB (AGC off; DNR on) - DNR (digital noise reduction): Built-in 2D/3D DNR - WDR (wide dynamic range): 110 dB - Flickerless Control: Automatic, 50 Hz, 60 Hz modes - Image Rotation: Flip, Mirror, and 180° rotation - Image Setting: Manual tuning with saturation, sharpness, and contrast - AGC (auto gain control): 2X, 4X, 8X, 16X, 32X, 64X - BLC (back light compensation): High/Medium/Low Video Interface - Video Compression: H.264 (ISO/IEC 14496-10) or MJPEG - Video Output: via Ethernet - Video Streams: 3 independent H.264 or MJPEG video streams - Video Resolution and FPS (frames per second) - Video Viewing DynaStream™ support for changing the video frame rate automatically CBR Pro™ for good image quality in limited bandwidth transmissions 3 privacy mask areas provided Adjustable image size and quality Timestamp and text overlay OSD (On Screen Display) position adjustable Maximum of 5 simultaneous unicast connections, 50 multicast clients Audio Interface - Audio Inputs: 1 x line-in, with RCA connector - Audio Format: Mono, PCM (G.711) Camera Software Development - Video Standards: ONVIF Profile S Camera Alarm Software Features - Intelligent Video: Camera tampering detection - Video Motion Detection: 3 independently configurable areas - Scheduling: Daily repeat timing schedule - Imaging: JPEG snapshots for pre/trigger/post alarm images - Custom Alarms: HTTP event servers for setting customized alarm actions - FTP Messaging: Automatic transfer of stored images via FTP as event-triggered actions Software Requirements - Memory Size: 1 GB - Operating System: Windows 7 or above - Browser: Internet Explorer 9.x or above - Multimedia: DirectX 9.0C or above Physical Characteristics - Housing Plastic top cover, metal bottom plate IP66 rain and dust protection IK10 vandal resistant protection Transparent PC cover - Dimensions: 110 x 47 mm (4.33 x 1.85 in) - Weight: 310 g (0.68 lb) - Installation: Panel mounting Environmental Limits - Operating Temperature: -25 to 55°C (-13 to 131°F) - Storage Temperature (package included): -40 to 85°C (-40 to 185°F) - Ambient Relative Humidity: 5 to 95% (non-condensing) - Ingress Protection: IEC 60529, IP66 - Vandal Resistance: EN 62262, IK10 - Altitude: 2000 m Standards and Certifications - EMI: CISPR 32, FCC Part 15B Class A - EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Signal: 2 kV IEC 61000-4-5 Surge: Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF - Freefall: IEC 60068-2-31 - Railway Fire Protection: EN 45545-2 - Safety: UL 62368-1 - Shock: IEC 60068-2-27, IEC 61373, EN 50155 - Vibration: IEC 60068-2-64, IEC 61373, EN 50155 - Railway: EN 50155 (complies with a portion of EN 50155 specifications) MTBF - Time: 1,944,687 hrs - Standards: Telcordia SR332

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

