

Artikelnr.: 385471

AWK-3131A-M12-RTG-JP-T - 802.11n-Eisenbahn-Zugangspunkt für den Innenbereich mit einem Funkgerät

ab 1.213,61 EUR

Artikelnr.: 385471
Versandgewicht: 1.00 kg
Hersteller: MOXA



 [Produktbeschreibung](#)

Die praxiserprobten Wireless-LAN-Produkte von Moxa ermöglichen es Betreibern, die Kommunikation zwischen den Waggons und zwischen den Zügen mit erhöhter Effizienz zu verwalten und hilfreiche Multimediale Dienste an Bord einzurichten, die die Sicherheit und den Komfort der Fahrgäste erhöhen. 802.11n Eisenbahn Onboard Single Radio Access Point/Client, M12, JP-Band, IP30, -40 bis 75°C Betriebstemperatur/WLAN Interface- WLAN Standards 802.11a/b/g/n/802.11i Wireless Security- Modulation Type DSSS OFDM 802.11b: CCK @ 11/5.5 Mbps 802.11b: DQPSK @ 2 Mbps 802.11b: DBPSK @ 1 Mbps 802.11a/g: 64QAM @ 54/48 Mbps 802.11a/g: 16QAM @ 36/24 Mbps 802.11a/g: QPSK @ 18/12 Mbps 802.11a/g: BPSK @ 9/6 Mbps 802.11n: 64QAM @ 300 Mbps to BPSK @ 6.5 Mbps- Frequency Band for JP (20 MHz operating channels) 2.412 to 2.484 GHz (14 channels) 5.180 to 5.240 GHz (4 channels) 5.260 to 5.320 GHz (4 channels) 5.500 to 5.700 GHz (11 channels)- Wireless Security SSID broadcast enable/disable WEP encryption (64-bit and 128-bit) WPA/WPA2-Personal WPA/WPA2-Enterprise (IEEE 802.1X/RADIUS, TKIP, AES)- Transmission Rate 802.11b: 1 to 11 Mbps 802.11a/g: 6 to 54 Mbps 802.11n: 6.5 to 300 Mbps- Transmitter Power for 802.11a 23±1.5 dBm @ 6 to 24 Mbps 21±1.5 dBm @ 36 Mbps 20±1.5 dBm @ 48 Mbps 18±1.5 dBm @ 54 Mbps- Transmitter Power for 802.11n (5 GHz) 23±1.5 dBm @ MCS0 20 MHz 20±1.5 dBm @ MCS1 20 MHz 20±1.5 dBm @ MCS2 20 MHz 20±1.5 dBm @ MCS3 20 MHz 19±1.5 dBm @ MCS4 20 MHz 18±1.5 dBm @ MCS5 20 MHz 18±1.5 dBm @ MCS6 20 MHz 18±1.5 dBm @ MCS7 20 MHz 23±1.5 dBm @ MCS8 20 MHz 20±1.5 dBm @ MCS9 20 MHz 20±1.5 dBm @ MCS10 20 MHz 20±1.5 dBm @ MCS11 20 MHz 19±1.5 dBm @ MCS12 20 MHz 19±1.5 dBm @ MCS13 20 MHz 18±1.5 dBm @ MCS14 20 MHz 18±1.5 dBm @ MCS15 20 MHz 23±1.5 dBm @ MCS0 40 MHz 20±1.5 dBm @ MCS1 40 MHz 20±1.5 dBm @ MCS2 40 MHz 20±1.5 dBm @ MCS3 40 MHz 19±1.5 dBm @ MCS4 40 MHz 18±1.5 dBm @ MCS5 40 MHz 18±1.5 dBm @ MCS6 40 MHz 18±1.5 dBm @ MCS7 40 MHz 23±1.5 dBm @ MCS8 40 MHz 20±1.5 dBm @ MCS9 40 MHz 20±1.5 dBm @ MCS10 40 MHz 20±1.5 dBm @ MCS11 40 MHz 19±1.5 dBm @ MCS12 40 MHz 19±1.5 dBm @ MCS13 40 MHz 18±1.5 dBm @ MCS14 40 MHz 18±1.5 dBm @ MCS15 40 MHz- Transmitter Power for 802.11b 26±1.5 dBm @ 1 Mbps 26±1.5 dBm @ 2 Mbps 26±1.5 dBm @ 5.5 Mbps 25±1.5 dBm @ 11 Mbps- Transmitter Power for 802.11g 23±1.5 dBm @ 6 to 24 Mbps 21±1.5 dBm @ 36 Mbps 19±1.5 dBm @ 48 Mbps 18±1.5 dBm @ 54 Mbps- Transmitter Power for 802.11n (2.4 GHz) 23±1.5 dBm @ MCS0 20 MHz 21±1.5 dBm @ MCS1 20 MHz 21±1.5 dBm @ MCS2 20 MHz 21±1.5 dBm @ MCS3 20 MHz 21±1.5 dBm @ MCS4 20 MHz 19±1.5 dBm @ MCS5 20 MHz 18±1.5 dBm @ MCS6 20 MHz 18±1.5 dBm @ MCS7 20 MHz 23±1.5 dBm @ MCS8 20 MHz 21±1.5 dBm @ MCS9 20 MHz 21±1.5 dBm @ MCS10 20 MHz 21±1.5 dBm @ MCS11 20 MHz 20±1.5 dBm @ MCS12 20 MHz 19±1.5 dBm @ MCS13 20 MHz 19±1.5 dBm @ MCS14 20 MHz 18±1.5 dBm @ MCS15 40 MHz- Receiver Sensitivity for 802.11a (measured at 5.680 GHz) Typ. -90 @ 6 Mbps Typ. -88 @ 9 Mbps Typ. -88 @ 12 Mbps Typ. -85 @ 18 Mbps Typ. -81 @ 24 Mbps Typ. -78 @ 36 Mbps Typ. -74 @ 48 Mbps Typ. -74 @ 54 Mbps- Note Receiver Sensitivity for 802.11n (5 GHz; measured at 5.680 GHz) Typ. -88 dBm @ MCS0 20 MHz Typ. -85 dBm @ MCS1 20 MHz Typ. -82 dBm @ MCS2 20 MHz Typ. -79 dBm @ MCS3 20 MHz Typ. -76 dBm @ MCS4 20 MHz Typ. -71 dBm @ MCS5 20 MHz Typ. -70 dBm @ MCS6 20 MHz Typ. -69 dBm @ MCS7 20 MHz Typ. -95 dBm @ MCS8 20 MHz Typ. -91 dBm @ MCS9 20 MHz Typ. -87 dBm @ MCS10 20 MHz Typ. -80 dBm @ MCS11 20 MHz Typ. -78 dBm @ MCS12 20 MHz Typ. -74 dBm @ MCS13 20 MHz Typ. -72 dBm @ MCS14 20 MHz Typ. -71 dBm @ MCS15 20 MHz Typ. -84 dBm @ MCS0 40 MHz Typ. -81 dBm @ MCS1 40 MHz Typ. -77 dBm @ MCS2 40 MHz Typ. -75 dBm @ MCS3 40 MHz Typ. -71 dBm @ MCS4 40 MHz Typ. -67 dBm @ MCS5 40 MHz Typ. -64 dBm @ MCS6 40 MHz Typ. -63 dBm @ MCS7 40 MHz Typ. -90 dBm @ MCS8 40 MHz Typ. -85 dBm @ MCS9 40 MHz Typ. -82 dBm @ MCS10 40 MHz Typ. -81 dBm @ MCS11 40 MHz Typ. -77 dBm @ MCS12 40 MHz Typ. -73 dBm @ MCS13 40 MHz Typ. -71 dBm @ MCS14 40 MHz Note Typ. -68 dBm @ MCS15 40 MHz- Receiver Sensitivity for 802.11b (measured at 2.437 GHz) Typ. -93 dBm @ 1 Mbps Typ. -93 dBm @ 2 Mbps Typ. -93 dBm @ 5.5 Mbps Typ. -88 dBm @ 11 Mbps- Receiver Sensitivity for 802.11g (measured at 2.437 GHz) Typ. -88 dBm @ 6 Mbps Typ. -86 dBm @ 9 Mbps Typ. -85 dBm @ 12 Mbps Typ. -85 dBm @ 18 Mbps Typ. -85 dBm @ 24 Mbps Typ. -82 dBm @ 36 Mbps Typ. -78 dBm @ 48 Mbps Typ. -74 dBm @ 54 Mbps- Receiver Sensitivity for 802.11n (2.4 GHz; measured at 2.437 GHz) Typ. -89 dBm @ MCS0 20 MHz Typ. -85 dBm @ MCS1 20 MHz Typ. -85 dBm @ MCS2 20 MHz Typ. -82 dBm @ MCS3 20 MHz Typ. -78 dBm @ MCS4 20 MHz Typ. -74 dBm @ MCS5 20 MHz Typ. -72 dBm @ MCS6 20 MHz Typ. -70 dBm @ MCS7 20 MHz Typ. -95 dBm @ MCS8 20 MHz Typ. -90 dBm @ MCS9 20 MHz Typ. -87 dBm @ MCS10 20 MHz Typ. -83 dBm @ MCS11 20 MHz Typ. -80 dBm @ MCS12 20 MHz Typ. -74 dBm @ MCS13 20 MHz Typ. -71 dBm @ MCS14 20 MHz Typ. -69 dBm @ MCS15 20 MHz Typ. -87 dBm @ MCS0 40 MHz Typ. -83 dBm @ MCS1 40 MHz Typ. -83 dBm @ MCS2 40 MHz Typ. -80 dBm @ MCS3 40 MHz Typ. -76 dBm @ MCS4 40 MHz Typ. -73 dBm @ MCS5 40 MHz Typ. -69 dBm @ MCS6 40 MHz Typ. -67 dBm @ MCS7 40 MHz Typ. -93 dBm @ MCS8 40 MHz Typ. -88 dBm @ MCS9 40 MHz Typ. -85 dBm @ MCS10 40 MHz Typ. -82 dBm @ MCS11 40 MHz Typ. -78 dBm @ MCS12 40 MHz Typ. -73 dBm @ MCS13 40 MHz Typ. -69 dBm @ MCS14 40 MHz Typ. -67 dBm @ MCS15 40 MHz- WLAN Operation Mode Access point, Client, Client-Router, Sniffer- Antenna Connectors QMA Ethernet Interface- PoE Ports (10/100BaseT(X), M12 D-coded 4-pin female connector) 1, AWK-3131A-M12-RTG only- Standards IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3af for PoE IEEE 802.1Q for VLAN Tagging- 10/100BaseT(X) Ports (M12 D-coded 4-pin female connector) 1, 10/100BaseT(X) auto negotiation speed, F/H duplex mode, and auto MDI/MDI-X connection (AWK-3131A-M12-RTG only)- 100BaseFX Ports (single-mode SC connector) 1, AWK-3131A-SSC-RTG only Ethernet Software Features- Management General: Proxy ARP, DNS, HTTP, HTTPS, IP, ICMP, SNT, TCP, UDP, RADIUS, SNMP, PPPoE, DHCP- only: ARP, BOOTP, DHCP, STP/RSTP (IEEE 802.1D/w)- Security RADIUS Firewall- Filter MAC/IP Protocol/Port-based Serial Interface- Console Port RS-232 (RJ45-type) LED Interface- LED Indicators PWR1, PWR2, PoE*, FAULT, STATE, SIGNAL, CLIENT, WLAN, LAN (AWK-3131A-M12-RTG only), 100M (AWK-3131A-SSC-RTG only)* PoE is only available for the AWK-3131A-M12-RTG Input/Output Interface- Digital Inputs 2+13 to +30 V for state 1+3 to -30 V for state 0 Max. input current: 8 mA- Alarm Contact Channels Relay output with current carrying capacity of 1 A @ 24 VDC- Buttons Reset button Physical Characteristics- Housing Metal- IP Rating IP30- Dimensions 52.9 x 151.9 x 127.4 mm (2.08 x 5.98 x 5.02 in)- Weight 850 g (1.87 lb)- Installation DIN-rail mounting, Wall mounting (with optional kit) Power Parameters- Input Current AWK-3131A-M12-RTG: 0.85 A @ 12 VDC, 0.22 A @ 48 VDC AWK-3131A-SSC-RTG: 1.0 A @ 12 VDC, 0.27 A @ 48 VDC- Input Voltage 12 to 48 VDC, Redundant dual inputs, 48 VDC Power-over-Ethernet- Power Connector 1 removable 10-contact terminal block(s)- Power Consumption AWK-3131A-M12-RTG: Maximum 10.5 W- Reverse Polarity Protection Supported Environmental Limits- Operating Temperature Wide Temp. Models: -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 61000-6-2/-6-4- EMI CISPR 32, FCC Part 15B Class B- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8- Railway EN 50155, EN 50121-4- Railway Fire Protection EN 45545-2- Radio EN 301 489-1/17, EN 300 328, EN 301 893, MIC, FCC ID SLE-WAPN008, SRRC, NCC, IDA- Safety UL 60950-1, IEC 60950-1, EN 60950-1 (LVD) MTBF- Time AWK-3131A-M12-RTG: 552,454 hrs AWK-3131A-SSC-RTG: 528,478 hrs- Standards Telcordia SR332

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

