

Artikelnr.: 384672

NPORT IA-5150I-T - 1-Port RS-232/422/485 Device Server mit 2 10100BaseT(X) Ports

ab **433,81 EUR**

Artikelnr.: 384672
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Ethernet Interface- 10/100BaseT(X) Ports (RJ45 connector) 2 (1 IP, Ethernet cascade) - Magnetic Isolation Protection 1.5 kV (built-in) - 100BaseFX Ports (multi-mode SC connector) NPort IA-5150/5150I-M-SC models: 1NPort IA-5150-M-ST models: 1 - 100BaseFX Ports (single-mode SC connector) NPort IA-5150/5150I-S-SC models: 1 Ethernet Software Features- Configuration Options Web Console (HTTP) Windows Utility Telnet Console Serial Console - Management: DHCP Client, IPv4, SMTP, SNMPv1, Telnet, ARP, BOOTP, DNS, HTTP, TCP/IP, UDP, ICMP, Rtelnet- Windows Real COM Drivers Windows 11, 10, 8.1, 8, 7, Vista, XP, ME, 98 and 95 Windows Server 2022, 2019, 2016, 2012 R2, 2012, 2008 R2, 2008, 2003, 2000 and NT Windows Embedded CE 5.0 and 6.0, Windows XP Embedded- Linux Real TTY Drivers Kernel versions: 6.x, 5.x, 4.x, 3.x, 2.6.x, and 2.4.x- Fixed TTY Drivers macOS versions: 14, 13, 12, 11, and 10.1x SCO UNIX, SCO OpenServer, UnixWare 7, QNX 4.25, QNX 6, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS X - Arm®-based Platform Support Windows 11 Linux Kernel 6.x, 5.x, and 4.x macOS 14, 13, 12, and 11 - Virtual Machine VMWare ESXi (Windows 11/10) VMware Fusion (Windows on macOS 14, 13, 12, 11, and 10.1x) Parallels Desktop (Windows on macOS 14, 13, 12, 11, and 10.1x) - Android API Android 3.1.x and later - Time Management SNTP - MIB RFC1213, RFC1317 Security Functions- Authentication: Local database (password only) Serial Interface- Connector NPort IA-5150/5150I models: DB9 male for RS-232 and terminal block for RS-422/485 NPort IA-5250/5250I models: DB9 male for RS-232/422/485 - No. of Ports NPort IA-5150/5150I models: 1NPort IA-5250/5250I models: 2 - Serial Standards RS-232 RS-422 RS-485 - Baudrate Supports standard baudrates (unit=bps): 110, 134, 150, 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 230400 - Data Bits 5, 6, 7, 8 - Parity None, Even, Odd, Space, Mark - Stop Bits 1, 1.5, 2 - Flow Control RTS/CTS (RS-232 only) DTR/DSR (RS-232 only) XON/XOFF - Terminator for RS-485 120 ohms - Pull High/Low Resistor for RS-485 1 kilo-ohm, 150 kilo-ohms - Isolation I models: 2 kV - RS-485 Data Direction Control ADDC (automatic data direction control) Serial Signals- RS-232 Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND - RS-422 Tx+, Tx-, Rx+, Rx-, GND - RS-485 4w Tx+, Tx-, Rx+, Rx-, GND - RS-485 2w Data+, Data-, GND Power Parameters- Input Voltage 12 to 48 VDC - Input Current NPort IA-5150/IA-5150I-T/IA-5250/IA-5250I-T: 435 mA @ 12 VDC NPort IA-5150/IA-5150I-T/IA-5150I-S-SC/IA-5150I-M-SC/IA-5150I-M-SC-T/IA-5150I-S-SC/IA-5150I-S-SC-T: 555 mA @ 12 VDC NPort IA-5250/IA-5250I-T/IA-5150I-M-SC/IA-5150I-M-SC-T/IA-5150I-M-ST/IA-5150I-M-ST-T: 510 mA @ 12 VDC - No. of Power Inputs 2 - Power Connector Terminal block Physical Characteristics - Housing Plastic - IP Rating IP30 - Dimensions 29 x 89.2 x 118.5 mm (0.82 x 3.51 x 4.57 in) - Weight NPort IA-5150/5150I: 360 g (0.79 lb) NPort IA-5250/5250I: 380 g (0.84 lb) - Installation DIN-rail mounting Environmental Limits- Operating Temperature Standard models: 0 to 60°C (32 to 140°F) Wide Temp. models: -40 to 75°C (-40 to 167°F) - Storage Temperature (package included) -40 to 85°C (-40 to 167°F) - Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC: EN 55032/35 - EMI: CISPR 32, FCC Part 15B Class A - EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFM IEC 61000-4-11 - Safety IEC 60950-1 EN 60950-1 EN 62368-1 UL 508 - Maritime DNV - Hazardous Locations ATEX Class I Division 2 IECEx - Freefall: IEC 60068-2-32 - Shock: IEC 60068-2-27 - Vibration IEC 60068-2-6 IEC 60068-2-64 Declaration- Green Product: RoHS, CRoHS, WEEE MTBF- Time NPort IA-5150/IA-5150I models: 1,349,710 hrs NPort IA-5150-M-SC/I-M-ST/S-SC models: 1,175,887 hrs NPort IA-5150I-M-SC models: 768,343 hrs NPort IA-5150I-S-SC models: 763,707 hrs NPort IA-5250/IA-5250I models: 1,236,384 hrs - Standards Telcordia (Bellcore) Standard TR/SR

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

