

Artikelnr.: 384682

OBU-102-SS-ST - 2-Kanal-Glasfaser-Bypass-Einheit mit 4 Singlemode-Ports, ST

ab **1.128,19 EUR**

Artikelnr.: 384682
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Moxas Glasfaseradapter und Glasfaser-Bypass-Einheiten sind optionales Zubehör, das weitere Glasfaseranschlussoptionen für Moxas industrielle Ethernet-Switches bietet. 2-Kanal-Glasfaser-Bypass-Einheit mit 4 Singlemode-Ports, ST, -20 bis 70°C Betriebstemperatur Ethernet Interface- Single-Mode Fiber, ST Female Connector 4 Bypass Properties- Optical Switching Time 10 ms (max.)- Insertion Loss 1.6 dB (max.) Rotary Switch Configuration- Boot Delay Interval 10 steps, each step represents a 5 second delay Power Parameters- Input Voltage 12/24/48 VDC, Redundant dual inputs- Input Current 0.1 A @ 48 VDC- Reverse Polarity Protection Supported Physical Characteristics- Housing Metal- IP Rating IP30- Dimensions 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)- Weight 700 g (1.54 lb)- Installation DIN-rail mounting, Wall mounting (with optional kit) Environmental Limits- Operating Temperature -20 to 70°C (-4 to 158°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- Safety UL 508- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Freefall IEC 60068-2-31- Shock IEC 60068-2-27- Vibration IEC 60068-2-6

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

