

Artikelnr.: 385344

## MGATE EIP3270I - 2-Port EtherNet/IP-zu-DF1-Gateway mit 2 kV Isolierung

ab **613,08 EUR**

Artikelnr.: 385344  
Versandgewicht: 0.40 kg  
Hersteller: MOXA



### Produktbeschreibung

Die Ethernet/IP-Gateways von Moxa ermöglichen verschiedene Kommunikationsprotokollkonvertierungen in einem EtherNet/IP-Netzwerk. 2-Port-EtherNet/IP-zu-DF1-Gateway mit 2 kV Isolierung, 0 bis 60 °C Betriebstemperatur Ethernet Interface- 10/100BaseT(X) Ports (RJ45 connector) 2 Auto MDI/MDI-X connection Ethernet Software Features- Industrial Protocols Ethernet/IP (PCCC)- Configuration Options MGate Manager Telnet Console- Management ARP DHCP Client SNMP v1 TCP/IP Telnet UDP- MIB RFC1213, RFC1317 Serial Interface- No. of Ports 2- Connector 2 x DB9 male- Serial Standards RS-232 RS-422- Baudrate 1200 bps to 921.6 kbps- Data Bits 8- Parity None Even Odd- Stop Bits 1, 2- Flow Control RTS/CTS DTR/DSR (RS-232 only)- Isolation 2 kV Serial Signals- RS-232 Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND- RS-422 Tx+, Tx-, Rx+, Rx-, GND Serial Software Features- Industrial Protocols DF1 DF1 (Transparent)- Mode Full duplex- Max. No. of Client Connections 8 Power Parameters- Input Voltage 12 to 48 VDC- Input Current 510 mA @ 12 VDC Relays- Contact Current Rating Resistive load: 1 A @ 30 VDC Physical Characteristics- Housing Plastic top cover, metal bottom plate- IP Rating IP30- Dimensions (with ears) 29 x 89.2 x 124.5 mm (1.14 x 3.51 x 4.90 in)- Dimensions (without ears) 29 x 89.2 x 118.5 mm (1.14 x 3.51 x 4.67 in)- Weight 380 g (0.84 lb) Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 4 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFM IEC 61000-4-11- Safety IEC 60950-1 UL 60950-1 EN 62368-1 UL 508- Hazardous Locations ATEX Class I Division 2 IECEx- Freefall IEC 60068-2-32- Shock IEC 60068-2-27- Vibration IEC 60068-2-6 IEC 60068-2-64 MTBF- Time 1,204,573 hrs- Standards Telcordia SR332

### Technische Daten

Hier gehts zum Artikel  
Alle Informationen,  
tagesaktuelle Preise und  
Verfügbarkeiten

