

Artikelnr.: 385340

MGATE 5217I-600-T - 2-Port Modbus-zu-BACnet/IP-Gateway, 600 Punkte, 2kV Isolierung

ab **548,78 EUR**

Artikelnr.: 385340
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Ob einzelne oder mehrere serielle Ports, die Modbus TCP-Gateway-Lösungen von Moxa konvertieren Daten in Netzwerken zwischen Modbus RTU/ASCII, Modbus TCP, DNP3, CANopen, J1939, PROFIBUS, BACnet/IP, IEC 101/104 und IEC 61850 und machen Konfiguration, Fehlerbehebung und Konvertierung schnell und einfach. 2-Port-Modbus-zu-BACnet/IP-Gateway, 600 Punkte, 2 kV Isolierung, 12 bis 48 VDC, 24 VAC, -40 bis 75 °C Betriebstemperatur Ethernet Interface- 10/100BaseT(X) Ports (RJ45 connector) 2 Auto MDI/MDI-X connection- Magnetic Isolation Protection 1.5 kV (built-in) Ethernet Software Features- Industrial Protocols Modbus TCP Client (Master) BACnet/IP Server (Slave)- Configuration Options Web Console (HTTP/HTTPS) Device Search Utility (DSU) Telnet Console- Management ARP DHCP Client DNS HTTP TFTP SMT P S N M P Trap SNMP v1/v2c/v3 TCP/IP Telnet UDP NTP Client- MIB RFC1213, RFC1317- Time Management NTP Client Security Functions- Authentication Local database- Encryption HTTPS AES-128 AES-256 SHA-256- Security Protocols SNMP v3 SNMP v2c Trap HTTPS (TLS 1.2) Serial Interface- No. of Ports 2- Connector DB9 male - Serial Standards RS-232/422/485- Baudrate 50 bps to 921.6 kbps- Data Bits 7, 8- Parity None Even Odd Space Mark- Stop Bits 1, 2- Flow Control RTS Toggle (RS-232 only) RTS/CTS DTR/DSR- RS-485 Data Direction Control Automatic Data Direction Control (ADDC)- Pull High/Low Resistor for RS-485 1 kilo-ohm, 150 kilo-ohms- Terminator for RS-485 120 ohms- Isolation 2 kV (built-in) Serial Signals- RS-232 Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND- RS-422 Tx+, Tx-, Rx+, Rx-, GND- RS-485-2w Data+, Data-, GND- RS-485-4w Tx+, Tx-, Rx+, Rx-, GND Serial Software Features- Industrial Protocols Modbus RTU/ASCII Master Modbus RTU/ASCII- Mode Master- Functions Supported 1, 2, 3, 4, 5, 6, 16- Max. No. of Commands 600 Modbus TCP- Mode Client (Master)- Functions Supported 1, 2, 3, 4, 5, 6, 16- Max. No. of Server Connections 32- Max. No. of Commands 600 BACnet/IP- Mode Server (Slave)- Memory Size 600 points- Supported BACnet Object Binary Input Binary Output Binary Value Analog Input Analog Output Analog Value Multi-state Input Multi-state Output Multi-state Value Integer Value Positive Integer Value Power Parameters- Input Voltage 24 VAC 12 to 48 VDC- Input Current 300 mA @ 24 VAC 510 mA @ 12 VDC- Power Connector Screw-fastened Euroblock terminal Relays- Contact Current Rating Resistive load: 1 A @ 30 VDC Physical Characteristics- Housing Plastic- IP Rating IP30- Dimensions (without ears) 29 x 89.2 x 118.5 mm (1.14 x 3.51 x 4.67 in)- Dimensions (with ears) 29 x 89.2 x 124.5 mm (1.14 x 3.51 x 4.90 in)- Weight 380 g (0.84 lb) Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 60950-1 UL 62368-1 IEC 60950-1 IEC 62368-1- Freefall IEC 60068-2-32- Shock IEC 60068-2-27- Vibration IEC 60068-2-6 IEC 60068-2-64- International Approval KCMTBF- Time 1,277,500 hrs- Standards Telcordia SR332

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

