

Artikelnr.: 384648

NPORT 5110A-T - RS-232-Geräteserver mit 1 Anschluss und Überspannungsschutz

ab **200,13 EUR**

Artikelnr.: 384648
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Unsere NPort-Geräteserver machen Ihre seriellen Geräte im Handumdrehen netzwerkfähig. Durch ihre kompakte Größe eignen sie sich ideal für den Anschluss von Geräten wie Kartenlesern und Zahlungsterminals an ein IP-basiertes Ethernet-LAN. 1-Port RS-232-Geräteserver mit Überspannungsschutz, -40 bis 75 °C Betriebstemperatur Ethernet Interface-10/100BaseT(X) Ports (RJ45 connector) 1- Magnetic Isolation Protection 1.5 kV (built-in) Ethernet Software Features- Configuration Options Serial Console- Management DHCP Client ARP BOOT PDNS HTTP TFTP SFTP ICMP IPv4 LLDP SMT PTPSNMP v1/v2c TCP/IP Telnet UDP- Filter IGMP v1/v2- Windows Real COM Drivers Windows 11, 10, 8.1, 8, 7, Vista, XP, ME, 98, and 95 Windows Server 2022, 2019, 2016, 2012 R2, 2012, 2008 R2, 2008, 2003, 2000, and NT Windows Embedded CE 6.0 and 5.0, Windows XP Embedded- Linux Real TTY Drivers Kernel versions: 6.x, 5.x, 4.x, 3.x, 2.6.x, and 2.4.x- Fixed TTY Drivers macOS versions: 14, 13, 12, 11, and 10.1x SCO UNIX, SCO OpenServer, UnixWare 7, QNX 4.25, QNX 6, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS X- Arm@-based Platform Support Windows 11 Linux kernel 6.x, 5.x, and 4.x macOS 14, 13, 12, and 11- Virtual Machine VMWare ESXi (Windows 11/10) VMware Fusion (Windows on macOS 14, 13, 12, 11, and 10.1x) Parallels Desktop (Windows on macOS 14, 13, 12, 11, and 10.1x)- Android API Android 3.1.x and later- MIB RFC1213, RFC1317 Security Functions- Authentication Local database- Encryption HTTP AES-128 SHA-1 RSA-1024 SHA-256- Security Protocols HTTPS (TLS 1.2) Serial Interface- Connector DB9 male- No. of Ports 1- Serial Standards RS-232- Operation Modes Disabled Ethernet Modem Pair Connection Real COM Reverse Telnet RFC2217 TCP Client TCP Server UDP- Baudrate Supports standard baudrates (unit=bps): 50, 75, 110, 134, 150, 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 230.4k, 460.8k, 921.6k- Data Bits 5, 6, 7, 8- Stop Bits 1, 1.5, 2- Parity None, Even, Odd, Space, Mark- Flow Control RTS/CTS (RS-232 only) DTR/DSR (RS-232 only) XON/XOFF Serial Signals- RS-232 Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND Power Parameters- No. of Power Inputs 1- Input Current 82.5 mA @ ; 12 VDC- Input Voltage 12 to 48 VDC- Source of Input Power Power input jack Reliability- Automatic Reboot Trigger Built-in WDT Physical Characteristics- Housing Metal- Dimensions (with ears) 75.2 x 80 x 22 mm (2.96 x 3.15 x 0.87 in)- Dimensions (without ears) 52 x 80 x 22 mm (2.05 x 3.15 x 0.87 in)- Weight 340 g (0.75 lb)- Installation Desktop DIN-rail mounting (with optional kit) Wall mounting Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 75°C (-40 to 167°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 0.5 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m IEC 61000-4-8 PFM IEC 61000-4-11- Safety UL 60950-1 Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 2,231,530 hrs- Standards Telcordia (Bellcore) Standard TR/SR

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

