

Artikelnr.: 387897

## SFP-1G20BLC-T - WDM-Typ (BiDi) SFP-Modul mit 1 1000BaseSFP-Port mit LC-Anschluss

ab **1.093,13 EUR**

Artikelnr.: 387897  
Versandgewicht: 0.10 kg  
Hersteller: MOXA



### Produktbeschreibung

Moxas Small Form-Factor Pluggable Transceiver (SFP) Ethernet-Glasfasermodule für Gigabit-Ethernet bieten eine Abdeckung über eine Vielzahl von Kommunikationsdistanzen. Ethernet Interface- Ports 1 - Connectors Duplex LC connector Simplex LC connector (WDM-type only) - Optical Fiber Typical Distance: To reach the typical distance of specified fiber transceiver, please refer to formula:  $\text{Link budget (dB)} > \text{dispersion penalty (dB)} + \text{total link loss (dB)}$  Power Parameters- Power Consumption Max. 1 W Environmental Limits- Operating Temperature -40 to 85°C (-40 to 185°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- Safety UL 62368-1 IEC 62368-1 IEC 60825-1- EMC EN 55032/35- EMIFCC 15B Test Report ICES-003: 2020 Issue 7- EMS IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1V IEC 61000-4-8 PFMF: 1 A/m at 50 Hz IEC 61000-4-11 Voltage Dips and Interruption- Maritime DNV

### Technische Daten

**Hier gehts zum Artikel**  
Alle Informationen,  
tagesaktuelle Preise und  
Verfügbarkeiten

