

Artikelnr.: 385293

NPORT 6250-S-SC-T - 2-Port RS-232/422/485 auf Singlemode-Glasfaser (SC-Anschluss)

ab **585,57 EUR**

Artikelnr.: 385293
Versandgewicht: 0.30 kg
Hersteller: MOXA



Produktbeschreibung

Moxas Terminalserver sind mit den speziellen Funktionen und Sicherheitsmerkmalen ausgestattet, die erforderlich sind, um zuverlässige Terminalverbindungen zu einem Netzwerk herzustellen, und können verschiedene Geräte wie Terminals, Modems, Daten-Switches, Großrechner und POS-Geräte verbinden, um sie für Netzwerk-Hosts und -Prozesse verfügbar zu machen.

2-Port RS-232/422/485 to single-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature

Memory- SD Slot Up to 32 GB (SD 2.0 compatible)

Ethernet Interface- 100BaseFX Ports (single-mode SC connector)

1- Magnetic Isolation Protection 1.5 kV (built-in)- Optical Fiber Read more

Ethernet Software Features- Configuration Options

Web Console (HTTP/HTTPS)

Windows Utility

Device Search Utility (DSU)

MCC Tool

Serial Console

Telnet/SSH Console- Management

ARPBOOT

PDHCP Client

DNS

HTTP

ICMP

IPv4/IPv6

LLDP

PPPoE

SMTP

SNMPv1/v2c/v3

SNTPTCP/IP

Telnet

UDP- Windows Real COM Drivers

Windows 11/10/8.1/8/7/Vista/XP/ME/98/95

Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003

Windows Embedded CE 6.0/5.0, Windows XP Embedded- Linux Real TTY Drivers

Kernel versions 6.x, 5.x, 4.x, 3.x, 2.6.x, and 2.4.x- Fixed TTY Drivers

macOS Versions: 11.x, 10.12 to 10.15

SCO UNIX, SCO OpenServer, UnixWare 7, QNX 4.25, QNX 6.x, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS X- Arm®-based Platform

Support Linux Kernel 5.x/4.x- Virtual Machine

VMWare ESXi (Windows 11/10)

VMware Fusion (Windows on macOS 10.12 to 11.x)

Parallels Desktop (Windows on macOS 10.12 to 11.x)- Android API

Android 3.1.x and later- Time Management

SNTPT Client- MIB MIB-II- Unicast Routing

RIPV1/V2

Static Route

Security Functions- Authentication

Local database

RADIUS

TACACS+- Encryption

HTTPS

AES-128

AES-256

HMAC

RSA-1024

SHA-1

SHA-256

SHA-384- Security Protocols

HTTPS (TLS 1.2)

SNMPv3

SSHv2

Serial Interface- Connector

DB9 male- No. of Ports

2- Serial Standards

RS-232

RS-422

RS-485- Secure Operation

Modes

Reverse

SSH

Secure Pair Connection

Secure Real COM

Secure TCP Client

Secure TCP Server

SSH- Standard Operation

Modes

Disabled

Ethernet Modem

Pair Connection

PPP

Printer

Real COM

Reverse Telnet

RFC2217

TCP Client

TCP Server

Terminal

UDP- Baudrate

50 bps to 921.6 kbps (supports non-standard baudrates)- Data

Bits

5, 6, 7, 8- Stop

Bits

1, 1.5, 2- Flow Control

RTS/CTS

DTR/DSRXON/XOFF- Parity

None, Even, Odd, Space, Mark- Pull

High/Low

Resistor for RS-485

1 kilo-ohm, 150 kilo-ohms- RS-485

Data

Direction Control

Automatic

Data

Direction Control (ADDC)- Terminator

for RS-485

120 ohms

Serial

Signals- RS-232

TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND-

RS-422

Tx+, Tx-, Rx+, Rx-, GND-

RS-485-4w

Tx+, Tx-, Rx+, Rx-, GND-

RS-485-2w

Data+, Data-, GND

Power

Parameters- Input

Current

430 mA @ 12 to 48 VDC- Input

Voltage

12 to 48 VDC

Reliability- Automatic

Reboot

Trigger

Built-in

WDT- Alert

Tools

Built-in

buzzer and RTC (real-time clock)

Physical

Characteristics- Housing

Metal- Dimensions

(with ears)

101 x 111 x 29 mm (3.98 x 4.37 x 1.1 in)- Dimensions

(without ears)

77 x 111 x 29 mm (3.30 x 4.37 x 1.1 in)- Weight

240 g (0.53 lb)- Installation

Desktop

DIN-rail

mounting (with optional kit)

Wall mounting

Environmental

Limits- Operating

Temperature

-40 to 75°C (-40 to 167°F)- Storage

Temperature

(package included)

-40 to 75°C (-40 to 167°F)- Ambient

Relative Humidity

5 to 95% (non-condensing)

Standards and Certifications- EMC

EN 55032/35- EMI

CISPR 32, FCC

Part 15B

Class A- EMS

IEC 61000-4-2

ESD: Contact:

4 kV; Air:

8 kV

IEC 61000-4-3

RS: 80 MHz to 1 GHz: 3 V/m

IEC 61000-4-4

EFT: Power:

1 kV(AC), 0.5 kV(DC); Signal:

0.5 kV

IEC 61000-4-5

Surge: Power:

1 kV(AC), 0.5 kV(DC); Signal:

1 kV

IEC 61000-4-6

CS: 3 V

IEC 61000-4-8

PFM

IEC 61000-4-11- Traffic

Control

NEMA

TS2- Vibration

IEC 60068-2-6- Freefall

IEC 60068-2-34- Safety

UL 60950-1

UL 62368-1

Declaration- Green

Product

RoHS, CRoHS, WEEE

MTBF- Time

1,526,091 hrs- Standards

Telcordia (Bellcore)

Standard

TR/SR

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

