

Artikelnr.: 387709

TCF-142-M-ST-T - RS-232/422/485 auf Multimode-Glasfaser-Medienkonverter

ab **233,20 EUR**

Artikelnr.: 387709
Versandgewicht: 0.40 kg
Hersteller: MOXA



Produktbeschreibung

Moxas industrietaugliche Seriell-zu-Glasfaser-Konverter können RS-232/422/485 in Glasfaser konvertieren, was den Benutzern eine einfache und zuverlässige Möglichkeit bietet, mit ihren seriellen Geräten zu kommunizieren. RS-232/422/485 zu Multimode-Glasfaser-Medienkonverter mit Glasfaserring-Unterstützung und ST-Anschluss, -40 bis 75°C Betriebstemperatur Serial Interface- No. of Ports 2- Serial Standards RS-232 RS-422 RS-485- Baudrate 50 bps to 921.6 kbps (supports non-standard baudrates)- Flow Control ADDC (automatic data direction control) for RS-485- Pull High/Low Resistor for RS-485 1 kilo-ohm, 150 kilo-ohms- RS-485 Data Direction Control ADDC (automatic data direction control)- Terminator for RS-485 N/A, 120 ohms, 120 kilo-ohms- Connector Multi-mode ST connector- Latency 300 ns Serial Signals- RS-232 Tx, Rx, GND- RS-422 Tx+, Tx-, Rx+, Rx-, GND- RS-485-4w Tx+, Tx-, Rx+, Rx-, GND- RS-485-2w Data+, Data-, GND Power Parameters- No. of Power Inputs 1- Input Current 70 to 140 mA @ 12 to 48 VDC- Input Voltage 12 to 48 VDC- Overload Current Protection Supported- Power Connector Terminal block- Power Consumption 70 to 140 mA @ 12 to 48 VDC- Reverse Polarity Protection Supported Physical Characteristics- IP Rating IP30- Housing Metal- Dimensions (with ears) 90 x 100 x 22 mm (3.54 x 3.94 x 0.87 in)- Dimensions (without ears) 67 x 100 x 22 mm (2.64 x 3.94 x 0.87 in)- Weight 320 g (0.71 lb)- Installation Wall mounting Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 1 kV IEC 61000-4-5 Surge: Power: 1 kV IEC 61000-4-6 CS: 3 V IEC 61000-4-8 PFMF- Environmental Testing IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-3- Safety UL 60950-1- Vibration IEC 60068-2-6 MTBF- Time 780,480 hrs- Standards Telcordia (Bellcore), GB

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

