

Artikelnr.: 385905

VPOR P06HC-1V42M - EN 50155, HD-Bild, kubische IP-Kamera mit M12-Stecker, PoE, 4,2 mm Objektiv

ab **608,03 EUR**

Artikelnr.: 385905
Versandgewicht: 0.30 kg
Hersteller: MOXA



Produktbeschreibung

Unsere Auswahl an IP-Kameras umfasst Dome- und Box-Kameras sowie Kameras mit robustem Design. Sie erfüllen Teile der Norm EN 50155 und sind daher zuverlässig und liefern eine hervorragende Bildqualität, die für eine Reihe von Anwendungen geeignet ist. EN 50155, HD-Bild, kubische IP-Kamera mit M12-Anschluss, PoE, 4,2-mm-Objektiv, -40 bis 55°C Betriebstemperatur Ethernet Interface- PoE Ports (10/100BaseT(X), M12 D-coded 4-pin female connector) 1 Ethernet Software Features- Protocols TCP/IP, IPv4, UDP, HTTP, RTP/RTSP, ARP, UPnP, FTP, TFTP, SMTP, NTP Client, DNS, DDNS, QoS, IGMP v3, ICMP, SNMP v1/v2c/v3, DHCP Opt66/67, HTTPS Security Functions- Password User-level password protection- Filter IP address- Encryption HTTPS Power Parameters- No. of Power Inputs 1- Source of Input Power PoE (IEEE 802.3af)- Input Current 0.17 A @ 48 VDC Camera Characteristics- Sensor 1/2.7-in HD progressive scan CMOS- Lens f=4.2 mm, F1.8, Diagonal 87°, Horizontal 80°, Vertical 43°- Minimum Illumination Color: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec)- Synchronization Internal- White Balance ATW/AWB- Electronic Shutter Auto (1/30 to 1/25000 sec)- S/N Ratio Maximum 50 dB (AGC off; DNR on)- DNR (digital noise reduction) Built-in DNR- WDR (wide dynamic range) 110 dB- Flickerless Control Automatic, 50 Hz, 60 Hz modes- Image Rotation Flip, Mirror, and 180° rotation- Image Setting Manual tuning with saturation, sharpness, and contrast- AGC (auto gain control) 2X, 4X, 8X, 16X, 32X, 64X- BLC (back light compensation) High/Medium/Low Video Interface- Video Compression H.264 (ISO/IEC 14496-10) or MJPEG- Video Output via Ethernet- Video Streams 3 independent H.264 or MJPEG video streams- Video Resolution and FPS (frames per second) Read more- Video Viewing DynaStream™ support for changing the video frame rate automatically CBR Pro™ for good image quality in limited bandwidth transmissions 3 privacy mask areas provided Adjustable image size and quality Timestamp and text overlay OSD (On Screen Display) position adjustable Maximum of 5 simultaneous unicast connections, 50 multicast clients Camera Software Development- Video Standards ONVIF Profile S Camera Alarm Software Features- Intelligent Video Camera tampering detection- Video Motion Detection 3 independently configurable areas- Scheduling Daily repeat timing schedule- Imaging JPEG snapshots for pre/trigger/post alarm images- Custom Alarms HTTP event servers for setting customized alarm actions- FTP Messaging Automatic transfer of stored images via FTP as event-triggered actions Software Requirements- Memory Size 1 GB- Operating System Windows 7 or above- Browser Internet Explorer 9.x or above- Multimedia DirectX 9.0C or above Physical Characteristics- Housing Metal- Dimensions 60 x 60 x 74.6 mm (2.36 x 2.36 x 2.94 in)- Weight 300 g (0.66 lb)- Installation Flush mounting Environmental Limits- Operating Temperature -40 to 55°C (-40 to 131°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)- Ingress Protection IEC 60529, IP30 (provided screws are used to fill the camera housing screw holes)- Altitude 2000 m Standards and Certifications- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Signal: 2 kV IEC 61000-4-5 Surge: Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Freefall IEC 60068-2-31- Railway Fire Protection EN 45545-2- Safety UL 62368-1- Shock IEC 60068-2-27, IEC 61373, EN 50155- Vibration IEC 60068-2-64, IEC 61373, EN 50155- Railway EN 50155 (complies with a portion of EN 50155 specifications) MTBF- Time 692,847 hrs- Standards IEC 62380

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

