

Artikelnr.: 385827

VPORT P06-2M36M - EN 50155, 1080P, H.264MJPEG IP Kamera mit M12 Stecker

ab 769,48 EUR

Artikelnr.: 385827
Versandgewicht: 0.70 kg
Hersteller: MOXA



Produktbeschreibung

Memory- microSD Slot: SDXCInput/Output Interface- Digital Input Channels: 1- Digital Inputs: +13 to +30 V for state 1, -30 to +1 V for state 0, Max. input current: 8 mA- Connector: 5-pin A-coded male M12 connector with 20 cm cableEthernet Interface- PoE Ports (10/100BaseT(X), M12 D-coded 4-pin female connector)Ethernet Software Features- Protocols: TCP/IP, IPv4/IPv6, UDP, HTTP, RTP/RTSP, ARP, UPnP, FTP, TFTP, NTP Client, DNS, QoS, IGMP v3, ICMP, SNMPv1/v2c/v3, DHCP Opt66/67, HTTPS, SIPSecurity Functions- Password: User-level password protection- Filter: IP address- Encryption: HTTPS, SSHPower Parameters- No. of Power Inputs: 1- Source of Input Power: PoE (IEEE 802.3af)- Input Current: 0.17 A @ 48 VDCCamera Characteristics- Sensor: 1/3-in 1080P progressive scan CMOS- Lens: f=3.6 mm, F1.6, Diagonal 99°, Horizontal 70°, Vertical 39°- Minimum Illumination: Color: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec)- Synchronization: Internal- White Balance: ATW/AWB- Electronic Shutter: Auto, Fixed (1/30 to 1/25000 sec)- S/N Ratio: Maximum 50 dB (AGC off; DNR on)- DNR (digital noise reduction): Built-in 2D/3D DNR- WDR (wide dynamic range): 100 dB- AGC (auto gain control): 2X, 4X, 8X, 16X- Flickerless Control: Automatic, 50 Hz, 60 Hz modes- Image Rotation: Flip, Mirror, 90°, 180°, 270° rotation- Image Setting: Manual tuning with saturation, sharpness, and contrast- Camera Angle: Pan: ±15°, Tilt: 0° to 90° (controlled manually)Video Interface- Video Compression: H.264 (ISO/IEC 14496-10) or MJPEG- Video Output: via Ethernet- Video Streams: 4 independent H.264 or MJPEG video streams- Video ViewingDynaStream™ support for changing the video frame rate automaticallyCBR Pro™ for good image quality in limited bandwidth transmissions3 privacy mask areas providedAdjustable image size and qualityTimestamp and text overlayOSD (On Screen Display) position adjustableMaximum of 10 simultaneous unicast connections, 50 multicast clientsAudio Interface- Audio Format: Mono, PCM (G.711), AAC- Audio Inputs: 1 x built-in microphoneCamera Software Development- Video Standards: ONVIF Profile SCamera Alarm Software Features- Intelligent Video: Camera tampering detection- Video Motion Detection: 3 independently configurable areas- Scheduling: Daily repeat timing schedule- Imaging: JPEG snapshots for pre/trigger/post alarm images- Custom Alarms: HTTP event servers for setting customized alarm actions- FTP Messaging: Automatic transfer of stored images via FTP as event-triggered actions- Pre-Alarm Buffer: 50 MB video buffer for JPEG snapshot images- Video Recording: Event recordings stored on the SD cardSoftware Requirements- Memory Size: 2 GB- Operating System: Windows 7 or above- Browser: Internet Explorer 9.x or above- Multimedia: DirectX 9.0C or abovePhysical Characteristics- HousingIP66 rain and dust protectionMetal housing, PC dome coverIK8 vandal resistant protection- Dimensions: 110 x 115.5 x 61.8 mm (4.33 x 4.53 x 2.43 in)- Weight: 620 g (1.37 lb)- Installation: Panel mounting- Protection: PCB conformal coating is optional and provided on request. If conformal coating is required, please contact Moxa.Environmental Limits- Operating Temperature: -25 to 55°C (-13 to 131°F)- Storage Temperature (package included): -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity: 5 to 95% (non-condensing)- Ingress Protection: IEC 60529, IP66- Vandal Resistance: EN 62262, IK8- Altitude: 2000 mStandards and Certifications- EMI: CISPR 32, FCC Part 15B Class A- EMSIEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/mIEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kVIEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kVIEC 61000-4-6 CS: 10 VIEC 61000-4-8 PFMF- Freefall: IEC 60068-2-31- Railway Fire Protection: EN 45545-2- Safety: UL 62368-1- Shock: IEC 60068-2-27, IEC 61373, EN 50155- Vibration: IEC 60068-2-64, IEC 61373, EN 50155- Railway: EN 50155 (complies with a portion of EN 50155 specifications)MTBF- Time: 1,050,590 hrs- Standards: Telcordia SR332

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

