

Artikelnr.: 385742

## VPORT P16-2MR36M-T - EN50155, Tag-Nacht, IR, 1080P IP Kamera

ab 1.029,08 EUR

Artikelnr.: 385742  
Versandgewicht: 0.90 kg  
Hersteller: MOXA



### Produktbeschreibung

Unsere Auswahl an IP-Kameras umfasst Dome- und Box-Kameras sowie Kameras mit robustem Design. Sie erfüllen Teile der Norm EN 50155 und bieten somit eine zuverlässige Leistung und eine hervorragende Bildqualität, die für eine Reihe von Anwendungen geeignet ist. EN50155, Tag & Nacht, IR, 1080P IP-Kamera, 3,6 mm Objektiv, PoE, M12-Anschluss, -40 bis 70°C Betriebstemperatur, Memory- microSD Slot: SDXC, Input/Output Interface- Digital Input Channels: 1- Digital Inputs: +13 to +30 V for state 1, -30 to +1 V for state 0, Max. input current: 8 mA- Connector: 5-pin A-coded male M12 connector with 20 cm cable Ethernet Interface- PoE Ports (10/100BaseT(X), M12 D-coded 4-pin female connector): 1- Standards: IEEE 802.3af for PoE Ethernet Software Features- Protocols: TCP/IP, IPv4/IPv6, UDP, HTTP, RTP/RTSP, ARP, UPnP, FTP, TFTP, SMTP, NTP Client, DNS, DDNS, QoS, IGMP v3, ICMP, SNMPv1/v2c/v3, DHCP Opt66/67, HTTP Security Functions- Password: User-level password protection- Filter: IP address- Encryption: HTTPS Power Parameters- No. of Power Inputs: 1- Source of Input Power: PoE (IEEE 802.3af)- Input Current: 0.26 A @ 48 VDC Camera Characteristics- Sensor: 1/3-in 1080P progressive scan CMOS- Lens: f=3,6 mm, F1.6, Diagonal 99°, Horizontal 70°, Vertical 39°- Minimum Illumination Color: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec) B/W: 0.05 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec) Note: 0 lux if IR illuminator is on- Camera Angle: Pan 350°, Tilt 65° (controlled manually)- Day & Night: Auto/Color/BW; ICR control- Synchronization- Internal: White Balance- ATW/AWB: Electronic Shutter- Auto, Fixed (1/30 to 1/25000 sec)- S/N Ratio: Maximum 50 dB (AGC off; DNR on)- ICR Control: Auto (light sensor control) or DI control- IR Illumination: IR LED illuminators, 5-meter (max.) effective distance; On/Off controlled manually (night mode) or by the light sensor- DNR (digital noise reduction): Built-in 2D/3D DNR- WDR (wide dynamic range): 100 dB- AGC (auto gain control): 2X, 4X, 8X, 16X- Flickerless Control: Automatic, 50 Hz, 60 Hz modes- Image Rotation: Flip, Mirror, 90°, 180°, 270° rotation- Image Setting: Manual tuning with saturation, sharpness, and contrast Video Interface- Video Compression: H.264 (ISO/IEC 14496-10) or MJPEG- Video Output: via Ethernet- Video Streams: 4 independent H.264 or MJPEG video streams- Video Viewing DynaStream™ support for changing the video frame rate automatically CBR Pro™ for good image quality in limited bandwidth transmissions 3 privacy mask areas provided Adjustable image size and quality Timestamp and text overlay OSD (On Screen Display) position adjustable Maximum of 5 simultaneous unicast connections, 50 multicast clients Audio Interface- Audio Format: Mono, PCM (G.711), AAC- Audio Inputs: 1 x built-in microphone Camera Software Development- Video Standards: ONVIF Profile S Camera Alarm Software Features- Intelligent Video: Camera tampering detection- Video Motion Detection: 3 independently configurable areas- Shock Detection: Built-in G sensor- Scheduling: Daily repeat timing schedule- Imaging: JPEG snapshots for pre/trigger/post alarm images- Custom Alarms: HTTP event servers for setting customized alarm actions- Email/FTP Messaging: Automatic transfer of stored images via email or FTP as event-triggered actions- Pre-Alarm Buffer: 50 MB video buffer for JPEG snapshot images- Video Recording: Event recordings stored on the SD card Software Requirements- Memory Size: 2 GB- Operating System: Windows 7 or above- Browser: Internet Explorer 9.x or above- Multimedia: DirectX 9.0C or above Physical Characteristics- Housing IP66 rain and dust protection Metal housing, PC dome cover IK8 vandal resistant protection- Dimensions: 125 x 125 x 120.7 mm (4.92 x 4.92 x 4.8 in)- Weight: 890 g (1.96 lb)- Installation: Panel mounting Environmental Limits- Operating Temperature: -40 to 70°C (-40 to 158°F)- Storage Temperature (package included): -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity: 5 to 95% (non-condensing)- Ingress Protection: IEC 60529, IP66- Salt Spray Test: ASTM-B117- Vandal Resistance: EN 62262, IK8- Altitude: 2000 m Standards and Certifications- EMI: CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Freefall: IEC 60068-2-31- Railway Fire Protection: EN 45545-2- Safety: UL 60950-1- Shock: IEC 60068-2-27, IEC 61373, EN 5015- Vibration: IEC 60068-2-64, IEC 61373, EN 50155- Railway: EN 50155 (complies with a portion of EN 50155 specifications) MTBF- Time: 997,474 hrs- Standards: Telcordia SR332

### Technische Daten

Hier gehts zum Artikel  
Alle Informationen,  
tagesaktuelle Preise und  
Verfügbarkeiten

