

Artikelnr.: 391801

DEC2770 - OPNsense® Rack-Sicherheitsanwendung, 7x 2.5GbE

ab **1.405,91 EUR**

Artikelnr.: 391801
Versandgewicht: 3.00 kg
Hersteller: Deciso



Produktbeschreibung

DEC2770 - OPNsense® Rack Security Appliance Unerreicht in seiner Klasse Bis zu 10 Gigabit Leistung in einem 1U Rack. Voll ausgestattet, ideal für KMUs und Zweigstellen. Mit bis zu 7x 2.5GbE! (DEC2770) Software- Preinstallated software OPNsense®- License Open Source + 1 year free Business Edition Hardware Specifications- Typical Applications Firewall / Routing, VPN, IDPS- SFP+ Ports [10Gbps] 2 - 2.5 GbE RJ45 Ports [100/1000/2500Mbps] 7- USB 3.0 Ports 1 - Console Port 1 - Internal Storage 256GB M.2. Solid State Flash-Memory 8GB DDR4- CPU Cores 4 (max frequency 2.2Ghz)- Virtual Interfaces (802.1q VLANs) 1 4093 System Performance- Firewall Throughput 10Gbps - Firewall Packets Per Second 830Kpps - Firewall Port to Port Throughput 8.5Gbps- Firewall Port to Port Packets Per Second 719000- Concurrent Sessions 7000000 - Firewall Latency (average) 150us- Firewall Policies (Recommended Maximum) 1 10000- IPsec VPN Throughput (AES256GCM16) 1.2Gbps- IPsec VPN Packet Per Second (AES256GCM16) 107Kpps- OpenVPN SSL Throughput (AES256GCM16) 500Mbps- OpenVPN Packet Per Second (AES256GCM16) 42Kpps- Threat Protection Throughput Packet Per Second 85Kpps- Threat Protection Throughput ~1Gbps - High Availability with State Synchronisation Requires Two- Dimensions Height x Width x Length (inches) 1.75 x 19 x 9.53 (8.43 excl. panel) 1.75 x 19 x 9.53 (8.43 excl. panel)- Form Factor 19" Rackmountable- Weight (appliance only) 2.75Kg Environment- Power Requirements 100-240VAC, 50-60Hz- Maximum Current (AC) 0.8A- Power Consumption (Typical) 20W- Heat Dissipation (Typical) 68.3 BTU/hr- Operating Temperature 0 to +45°C- Storage Temperature -20 to +70°C- Humidity 10-90% non-condensing Regulatory Compliance- FCC part 15 Class A, CE, Rohs

Technische Daten

Hier gehts zum Artikel
Alle Informationen,
tagesaktuelle Preise und
Verfügbarkeiten

