

Artikelnr.: 395762

## PR3PWAU3 - AU-Netzteil, 62W

ab **22,17 EUR**

Artikelnr.: 395762  
Versandgewicht: 0.40 kg  
Hersteller: Teltonika



### Produktbeschreibung

Technical Data- GENERAL- Input voltage: 100 – 240 VAC- Input frequency: 50 / 60 Hz- Input current: 1.5 A- Input connector: AU (Type I)- Output voltage: 48 VDC- Output current: 1.3 A- Output connector: 4-pin, 3 mm pitch- Weight: 360 g- ADDITIONAL- Input voltage range: 90 – 264 VAC- Input frequency range: 47 – 63 Hz- Maximum input inrush current: 50 A- Output voltage maximum deviation: 45.6 – 50.4 VDC- Short circuit protection: ja- HIPOT (dielectric withstand test): Primary to Secondary: 4000 VDC- MTBF: 50000 h- Certification: Safety: AS/NZS 61558.2.16:2010, EMC: AS/NZS CISPR 14.1:2013, EN 55032:2012+AC:2013, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010+A1:2015

### Technische Daten

**Hier gehts zum Artikel**  
Alle Informationen,  
tagesaktuelle Preise und  
Verfügbarkeiten

