

# **PRA2414**

### **Key Features:**

- 14 dBi Directional Gain
- Integrated enclosure
- Special Outdoor Weatherproof Enclosure Dedicated for Mikrotik RouterBOARDs
- High Quality Construction
- Horizontal or Vertical Polarization
- Heavy-Duty Mounting Elements
- Easy Elevation and Tilt Adjustment
- 5 Years Warranty
- Designed for All Weather Operation



### **Applications:**

- 2.4 GHz Band Wireless LAN
- IEEE 802.11b/g WLAN Systems
- Point to Point Application

#### Available in E version

PRA2414-e

Economy version with cable gland.


### **Description:**

Antenna with integrated enclosure working in 2.4 GHz band with 14 dBi gain that can be mounted for horizontal or vertical polarization. The range includes weatherproof outdoor enclosure with panel antenna and enough compartment for RouterBoard or any other electronic equipment. Enclosure is furnished with special RJ-45 waterproof ethernet connector with an easy connection to Internet Network and PoE. Perfectly designed for the properties and poet of the properties are properties.


environment without corrosion. High quality construction of pole mounting elements guarantee easy elevation and easy tilt down as well as rock-stable operation. It can be used as customer premise equipment and also as small base stations. Inside the enclosure are suitable posts for Mikrotik RouterBOARS 411 and 433 series.		

Electrical Properties		
Frequency	2.4 - 2.5 GHz	
Gain	14dBi	
Polarization	horizontal or vertical	
Beamwidth deg horizontal	38°	
Beamwidth deg vertical	38°	
VSWR	<2	
Impedance	50 ohm	
Front to back ratio	> 25 dB	
Lightning protection:	DC ground	
Enclosure Properties		
Technology:	Microstrip	
Material:	UV protected	
Colour:	Grey	
Min temperature:	-40°C / -40°F	
Max temperature:	80°C / 176°F	
Mechanical Properties		
Compatible with:	RB411 and RB433 series	
Input Connector	UFL, MMCX, RPSMA	
Enclosure Connector	Waterproof Ethernet Connector RJ45 (or cable gland optional)	
Outside Dimensions	270x270x75mm / 10,6x10,6x2,9"	
Weight	1,2kg / 2,65lbs	
Consideration and in the above without action		

Specification subject to change without notice.




VSWR



FPDF-extension (C) Trol Intermedia

## V-Plane



H-Plane