



TP-LINK

Gigabit Easy Smart Switch

TL-SG1016DE/TL-SG1024DE

Overview

The TL-SG1016DE/TL-SG1024DE 16-Port/24-Port Gigabit Easy Smart switch is an ideal upgrade from an unmanaged switch, designed for Small and Medium Business networks that require simple network management. Network administrators can effectively monitor traffic via Port Mirroring, Loop Prevention and Cable Diagnostics features. To optimize traffic on your business network, TL-SG1016DE/TL-SG1024DE offers both port and tag based QoS to keep latency-sensitive traffic moving smoothly and jitter-free. Additionally, port-based, tag-based and MTU VLAN can improve security and meet more network segmentation requirements. Moreover, with the innovative energy-efficient technology, the TL-SG1016DE/TL-SG1024DE can save up to 40% of power consumption, making it an eco-friendly solution for your business network.

Layer 2 Features

- IGMP Snooping
- Link Aggregation
- Port Mirroring
- Cable Test
- Loop Prevention

VLAN

- 32 VLANs
- MTU/Port/Tag VLAN

Quality of Service

- Port Based/802.1p Based priority
- 4 priority queues
- Rate Limit
- Storm Control

Green Technology

- Saving power 40%
- Recyclable packaging material



TP-LINK Gigabit Easy Smart Switch

TL-SG1016DE/TL-SG1024DE

Simple & Effective Management

TP-LINK Gigabit Easy Smart switch, TL-SG1016DE/TL-SG1024DE offers network monitoring for users to observe traffic behavior. With Port Mirroring, Loop Prevention and Cable Diagnostics features, TL-SG1016DE/TL-SG1024DE can identify and even locate connection problems on your business network. Moreover, administrators can designate the priority of the traffic based on Port Priority and 802.1P Priority, to ensure that voice and video are always clear, smooth and lag-free. Additionally, to improve security and network performance, TL-SG1016DE/TL-SG1024DE supports MTU VLAN, port-based VLAN and 802.1Q-based VLAN functions. TL-SG1016DE/TL-SG1024DE is an upgrade from the plug-and-play Unmanaged Switch, delivering great value while empowering your network and similarly delivering great value to the end user.

Go Green With Your Ethernet

You now have the choice to go green when upgrading a gigabit network! This new generation TL-SG1016DE/TL-SG1024DE 16-Port/24-Port Gigabit Easy Smart Switch features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network.

Power down Idle Ports

When a computer or network equipment is off, the corresponding port of a traditional switch will continue to consume considerable amounts of power. The TL-SG1016DE/TL-SG1024DE can automatically detect the link status of each port and reduce the power consumption of ports that are idle.

Power Budget According to Cable Length

Ideally, shorter cables would use less power because of less power degradation over their length; this is not the case with most devices as they will use the same amount of power across the cable regardless of whether it is 10 or 50 meters in length. The TL-SG1016DE/TL-SG1024DE analyzes the length of the Ethernet cable connected and adjusts the power usage accordingly, rather than keeping the power consumption in a conventional solution.



Ease of Use

TL-SG1016DE/TL-SG1024DE is easy to use and manage. Auto MDI/MDI-X crossover on all ports eliminate the need for crossover cables or uplink ports. Auto-negotiation on each port senses the link speed of a network device (either 10, 100, or 1000Mbps) and intelligently adjusts for compatibility and optimal performance. Compact size shell make it ideal for desktops with limited space while it is also Rackmountable, convenient and safe. Dynamic LED lights provide real-time work status display and basic fault diagnosis.



- Details: <http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included

Specifications

| Hardware Features & Performance | | |
|---------------------------------|--|---|
| Product Picture |  |  |
| Model | TL-SG1016DE | TL-SG1024DE |
| Physical Features | | |
| 10/100/1000Mbps RJ45 Ports | 16 | 24 |
| Power Supply | 100-240VAC, 50/60Hz | 100-240VAC, 50/60Hz |
| Fan Quantity | Fanless | Fanless |
| Certification | CE, FCC | CE, FCC |
| Dimensions (W x D x H) | 11.6 x 7.1 x 1.7 in. (284 x 180 x 44 mm), 13-inch Rack mount Steel Case, 1U Height | |
| Environment | Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing | |
| Performance | | |
| Switch Capacity | 32Gbps | 48Gbps |
| Forwarding Rate | 23.8Mpps | 35.7Mpps |
| Mac Address Table | 8k | 8k |
| Packet Buffer Memory | 512KB | 512KB |
| Jumbo Frame | 10240Bytes | 10240Bytes |

| Software Features | |
|--|--|
| <h4>L2 Switching Features</h4> <ul style="list-style-type: none"> IGMP Snooping <ul style="list-style-type: none"> IGMP Snooping v1/v2 Supports 128 Groups Link Aggregation <ul style="list-style-type: none"> Support static link aggregation Up to 8 aggregation groups, containing 4 ports per group Port Mirroring <ul style="list-style-type: none"> One-to-One Many-to-One Cable Test Loop Prevention <h4>VLAN</h4> <ul style="list-style-type: none"> Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN | <h4>Quality of Service(QoS)</h4> <ul style="list-style-type: none"> Support Port Based/802.1p Based priority Support 4 priority queues Rate Limit Storm Control <h4>Ethernet Protocols</h4> <ul style="list-style-type: none"> IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX/FX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.1q VLANs/VLAN tagging IEEE 802.1p QoS |

Ordering Information

| Host Switch | |
|---------------|--|
| Product Model | Description |
| TL-SG1016DE | 16-Port Gigabit Easy Smart Switch |
| TL-SG1024DE | 24-Port Gigabit Easy Smart Switch |
| Router | |
| Product Model | Description |
| TL-ER604W | SafeStream Wireless N Gigabit Broadband VPN Router |
| TL-ER608W | SafeStream Wireless N Gigabit Broadband VPN Router |