

# Delock M.2 SSD PCIe / NVMe Key M 2280 - 256 GB

**M.2 NVMe**

## Description

This flash module by Delock is a memory in the M.2 format for the PCIe / NVMe interface. With its 80 mm length, it has the form factor 2280. The module supports PCIe x4 and has the revision 3.0. The high read and write speed supports fast data transfer even for big amount of data, which is particularly important in the photo and video range.



**256 GB**

## Specification

- Connector: 1 x 67 pin M.2 Key M male
- Capacity: 256 GB
- Interface: PCIe x4 Rev. 3.0
- Controller: SMI SM2263XT
- Maximum read speed: 2000 MB/s
- Maximum write speed: 1200 MB/s
- Power consumption: max. 2 W
- MTBF: 1.000.000 hours
- Flash type: TLC
- Maximum write cycles: 1000
- Storage temperature: -55 °C ~ 115 °C
- Operating temperature: 0 °C ~ 70 °C
- Shock: 1500G
- Operating vibration: 16G
- Humidity: 5 ~ 98 %
- Supports TRIM
- Supports S.M.A.R.T.
- Supports NVM Express (NVMe) 1.3
- Dimensions (LxWxH): ca. 80.0 x 22.0 x 2.1 mm

## Item no. 54079

EAN: 4043619540792

Country of origin: China

Package: • Antistatic cover

## System requirements

- A free M.2 key M slot based on PCIe

## Package content

- M.2 SSD

## Images



Interface	
connector:	1 x 67 pin M.2 Key M male
Technical characteristics	
Operating temperature:	0° C - 70° C
Storage temperature:	-55 °C ~ 115 °C
Read:	2000 MB/s
Maximum power consumption:	2 W
Maximum write cycles:	1000
MTBF:	1.000.000 hours
Interface:	PCIe x4 Rev. 3.0
Shock:	1500 G
Write:	1200 MB/s
Capacity:	256 GB
Vibration:	16 G
Flash type:	TLC
Physical characteristics	
Length:	80.0 mm
Width:	22.0 mm
Height:	2.1 mm