



# Delock SATA 6 Gb/s DOM Module 16 GB MLC SATA Pin 8 power -40 °C ~ 85 °C

#### Description

This SATA DOM module by Delock is especially suitable for use in indutrial PCs und Server.


The module has an extended temperature range of -40  $^{\circ}$  C  $^{\sim}$  85  $^{\circ}$  C and is designed for use in harsh operating conditions.

Advantage: No additional power supply is required as power is provided via the SATA pin 8 connector. To use this application, a motherboard with SATA pin 8 connector is needed. The SATA pin 8 connector on the motherboard is of yellow colour. If no SATA pin 8 connector is available, this module can also be used via the standard SATA connector. For this purpose, the power supply is provided via the 3 pin power connector.




16 GB

### Schematic representation for SATA Pin 8



#### Standard power supply



#### **Specification**

· Capacity: 16 GB

• Interface: SATA 6 Gb/s

• Supports SATA pin 8 power

· Chip: Toshiba

• Flash type: MLC

Maximum performance: 100 MB/s read, 32 MB/s write

• Maximum write cycles: 3000

• Maximum power consumption: 1.8 W (5 V x 370 mA)

· Write protect: no

· ATA Security: yes

• S.M.A.R.T.: yes

Thermal sensor: yes

• Dimensions (WxLxH): 30 x 28.4 x 7.4 mm

• Vibration: 20G @ 7 ~ 2000 Hz

• Shock: 1500G @ 0.5 ms

#### Item no. 54810

EAN: 4043619548101

Country of origin: Taiwan, Republic

Of China

Package: • Antistatic cover





- MTBF: >3 million hours
- $\bullet$  Operation temperature: -40  $^{\circ}\text{C}$  ~ 85  $^{\circ}\text{C}$  Industrial grade
- Storage temperature: -55  $^{\circ}$  C  $^{\sim}$  95  $^{\circ}$  C

## System requirements

- A free SATA 8 pin or SATA 7 pin port
- For SATA 7 pin: power supply with a free 4 pin power connection

## Package content

- SATA DOM module
- Power cable

## **Images**











Technical characteristics	
Operating temperature:	-40°C - 85°C
Chipset:	Toshiba
Storage temperature:	-55°C - 95°C
Read:	100 MB/s
Maximum power consumption:	1.8 W
Maximum write cycles:	3000
MTBF:	3 million hours
Interface:	SATA 6.0 Gb/s
Shock:	1500 G @ 0.5 ms
Write:	32 MB/s
Capacity:	16 GB
Thermal sensor:	yes
Vibration:	20 G @ 7 ~ 2000 Hz
Password protection:	Yes
Delock iSmart:	Yes
Physical characteristics	
Length:	28.4 mm
Width:	30 mm
Height:	7.4 mm