

Delock Media Converter 100Base-FX SC MM 1310 nm 2 km

Description

This Delock Fast Ethernet Media Converter can be used to expand your network by an optical fiber interface.



Specification

- For Multi-Mode-Fiber, 1310 nm wavelength
- Distance up to 2 km with 50/125 μ m fiber
- Connector:
 - SC Duplex connector for 100 Base-FX
 - RJ45 connector for 10/100 Base-TX
- Transmission rate up to 100 Mb/s
- 6 LEDs for status monitoring
- DIP-Switch for configuration of LFP (Link Fault Pass Through), Half- or Full-Duplex, 10 or 100 Mb/s mode
- Power supply with 5 V included
- Power consumption: 2,5 W
- Dimensions (LxWxH): ca. 95 x 70 x 26 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 9.5 mm

Package content

- Media Converter
- Power supply
- User manual

Item no. 86216

EAN: 4043619862160

Country of origin: China

Package: White Box

Images

