





PTP/CLIENT ANTENNA

WiBOX SA M3-90-16X

WiBOX SA M3-90-16X is an X-polarity (slant +/-45) MIMO 2x2 sector antenna operating at a frequency range of: 3.4 - 3.8 GHz with 16 dBi gain. The antenna is predicted for point-to-multipoint (PMP) connections, can be used for covering medium and big areas as a base station for client stations or as the hotspot in schools, halls, stadiums or another public places. It can work indoor and outdoor (IP 67). It works with WIMAX and LTE (bands 22, 42, 43) systems. The antenna is integrated with the top quality WiBOX Extra Large box system.











Electrical specification

•	
Frequency	3.4 - 3.8 GHz
Gain	16 dBi ±1
VSWR	<1.60, max < 2.00
Beamwidth	8°/90°
Polarization	X
Cross-Polar Isolation	
Front-to-Back	> 30 dB
Separation between Connectors	> 25 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

-	
Dimensions	29.2 x 48.6 x 10.6 cm 11.5 x 19.13 x 4.17 inch
Weight	2.9 kg
Connector	RJ45
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 3400 3800 MHz Ox 16 dBi ±1
- Polarization X for the frequency of 3400 -3800 MHz
- > 0 x Connector SMA
- > Big, ergonomic and voluminous WiBOX Extra Large enclosure for radio equipment installation
- Outdoor Waterproof Enclosure WiBOX Extra Large
- Designed and resistant for any weather conditions
- >RJ45 Waterproof System
- Grounding system protecting against lighting DC Ground
- >36 Warranty Months

Systems

- LTE band 22, 42, 43
- > WLAN 3.6 GHz
- > WiMAX 3.5 GHz


Applications

> System Integration

Compatible with

Cambium Networks - PMP 450

Plots



STIPHING STATES