

Item no.: SC-DC2D479B

JVS-B62-DX - IP Surveillance Camera, 2 MP, Indoor/Outdoor

465,67 EUR

Item no.: SC-DC2D479B
 shipping weight: 4.90 kg
 Manufacturer: Jovision



Product Description

Jovision JVS-B62-DX - IP Surveillance Camera, 2 MP, Indoor/OutdoorThe STARLIGHT family is getting a new addition. Aside from the well-known good hardware and software, JVS-B62-DX also offers the STARLIGHT technology. It allows you to see a color image or stream not only in daylight but also at night. Especially at night, the smallest details play an important part.

The Jovision camera is very robust and is suitable for many application scenarios. It can be installed indoors as well as outdoors. You can, for example, monitor mansions, banks, hospitals, airports, prisons, parks, streets, train stations, stadiums and many more. Thanks to its sturdy enclosure with protection standard IP66, you can use this camera outdoors in all weather conditions.

- Resolution 1920 x 1080, 20x optical zoom
- 8x array LEDs, night vision up to 100 m
- Motion detection with alarm notification (one snapshot per mail)
- 1/2.8" progressive scan CMOS lens
- 2 MP with 20x optical zoom, 3D DNR, HLC/BLC, protection standard IP66
- Low bit rate, excellent image/stream quality in low light conditions
- STARLIGHT technology – color images in low light conditions

Specifications

Display

Image sensor: 1/2.8" CMOS

Resolution: 1920 x 1080

Resolution (megapixel): 2 MP

Compression: H.264 and H.265

Frame rate: up to 25 fps

Bit rate: 54

SNR (dB): 307 Kbps - 8 Mbps

Illumination: 0 lux (IR on)

Zoom: 20x optical zoom, 16x digital zoomLens

Focal length: 4.7 +/- 5 % - 94 +/- 5 % mm

IR LEDs: 8x array IR LEDs

IR range: up to 100 m

Pan speed: 0° - 200°/S

Tilt speed: 0° - 170°/S

Wave length: 850 nmFunction

Motion detection: yes

Email alarm: yes

Day & night: yes

Recording: yes (only NVR, Windows PC, NAS e.g. Synology, smartphone and tablet)

Pan/tilt : horizontal 0° - 360°, vertical 0° - 90°

Audio I/O (ext. mic.): yes

Audio codec: G711a, G711u

Privacy mask: yes (up to 4 areas)

Auto. exposure control: yes
Manual image adjustment: yes
Auto. white balance: yes
Image rotation: yes (90°, 180°, 270°)
Intercom function: no
Patrol guard: up to 255 positions (automatic sequence)Network
Ethernet: 10M/100M Ethernet, RJ45 port
Protocol: HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS, CloudSEE, Pelco-D (RS485)
Stream: 3x streams
Wi-Fi: no
LAN: yes
Onvif: Onvif 2.4
User: up to 13 users
Smartphone: iOS, Android (CloudSEE Int'l)General
Waterproof: IP66
Weight: 4800 g
Material: plastic
Working temperature range: -20 °C - 60 °C
Humidity: 0% - 90%
Power supply: DC 15 V / 3 A
Power consumption: < 30 W

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

