

Item no.: SC-DC2D479B

## JVS-B62-DX - IP Surveillance Camera, 2 MP, Indoor/Outdoor



# 465,67 EUR

Item no.: SC-DC2D479B  
 shipping weight: 4.90 kg  
 Manufacturer: Jovision

### Product Description

Jovision JVS-B62-DX - IP Surveillance Camera, 2 MP, Indoor/OutdoorThe STARLIGHT family is getting a new addition. Aside from the well-known good hardware and software, JVS-B62-DX also offers the STARLIGHT technology. It allows you to see a color image or stream not only in daylight but also at night. Especially at night, the smallest details play an important part.

The Jovision camera is very robust and is suitable for many application scenarios. It can be installed indoors as well as outdoors. You can, for example, monitor mansions, banks, hospitals, airports, prisons, parks, streets, train stations, stadiums and many more. Thanks to its sturdy enclosure with protection standard IP66, you can use this camera outdoors in all weather conditions.

- Resolution 1920 x 1080, 20x optical zoom
- 8x array LEDs, night vision up to 100 m
- Motion detection with alarm notification (one snapshot per mail)
- 1/2.8" progressive scan CMOS lens
- 2 MP with 20x optical zoom, 3D DNR, HLC/BLC, protection standard IP66
- Low bit rate, excellent image/stream quality in low light conditions
- STARLIGHT technology – color images in low light conditions

### Specifications

#### Display

Image sensor: 1/2.8" CMOS  
 Resolution: 1920 x 1080  
 Resolution (megapixel): 2 MP  
 Compression: H.264 and H.265  
 Frame rate: up to 25 fps  
 Bit rate: 54  
 SNR (dB): 307 Kbps - 8 Mbps  
 Illumination: 0 lux (IR on)  
 Zoom: 20x optical zoom, 16x digital zoomLens  
 Focal length: 4.7 +/- 5 % - 94 +/- 5 % mm  
 IR LEDs: 8x array IR LEDs  
 IR range: up to 100 m  
 Pan speed: 0° - 200°/S  
 Tilt speed: 0° - 170°/S  
 Wave length: 850 nmFunction  
 Motion detection: yes  
 Email alarm: yes  
 Day & night: yes  
 Recording: yes (only NVR, Windows PC, NAS e.g. Synology, smartphone and tablet)  
 Pan/tilt : horizontal 0° - 360°, vertical 0° - 90°  
 Audio I/O (ext. mic.): yes  
 Audio codec: G711a, G711u  
 Privacy mask: yes (up to 4 areas)

Auto. exposure control: yes  
Manual image adjustment: yes  
Auto. white balance: yes  
Image rotation: yes (90°, 180°, 270°)  
Intercom function: no  
Patrol guard: up to 255 positions (automatic sequence)Network  
Ethernet: 10M/100M Ethernet, RJ45 port  
Protocol: HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS, CloudSEE, Pelco-D (RS485)  
Stream: 3x streams  
Wi-Fi: no  
LAN: yes  
Onvif: Onvif 2.4  
User: up to 13 users  
Smartphone: iOS, Android (CloudSEE Int'l)General  
Waterproof: IP66  
Weight: 4800 g  
Material: plastic  
Working temperature range: -20 °C - 60 °C  
Humidity: 0% - 90%  
Power supply: DC 15 V / 3 A  
Power consumption: < 30 W

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

