Item no.: SC-2205-0614-0726

Alfa Network AIPC225VF-P, 2 Mega-pixel Full-HD Vari-Focal IP Cam

239,⁰⁶ EUR

Item no.: SC-2205-0614-0726
shipping weight: 1.30 kg
Manufacturer: ALFA Network

📄 Product Description

Alfa Network AIPC225VF-P, 2 Mega-pixel Full-HD Vari-Focal IP Camera with PoE, IP66 Weather-Resistant HousingFeatures:

- Full-HD Sony Exmor image sensor
- H.264, concurrent dual video stream
- 1080p resolution, 30 FPS real-time display
- Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45, micro-SD
- Built-in IR LED and ICR for day & night
- IEEE 802.3af Power over Ethernet support
- 3-axis mechanism camera viewing angle adjustment
- IP66 weather proof & vandal proof construction
- ONVIF & major NVR, CMS / VMS system compliant
- Various event trigger actions: FTP upload, mail alert, go to preset and tour

This product is subject to the GPL v2.

📄 Specifications

Image Capture:
Image sensor: 1/2.5 inch 2M Full-HD 1080p Sony Exmor progressive CMOS
Minimum illumination: 0.01 Lux / F 1.2 IR ON
Lens: 2.8 - 12 mm / F1.2
Night-vision: 30 pcs 850 nm IR LED
IR distance: 20 m, Physical IR cut filter supportVideo:
Encode format: H.264 Mainprofile / Baseline
Image resolution: 1920 x 1080
Frame rate(FPS): Max. 30 FPS real-time display
Data rate: 128 Kbps ~ 8 Mbps, CBR / VBR configurable
Image adjustment: contrast, brightness, saturationAudio:
Input: 1 x microphone input
Output: 1 x 3.5 mm phone jack line-out
Encode format: G.711 / G.726Network:
Ethernet: 10 Base-T / 100 Base-TX, RJ45 connector
Protocols: TCP/IP, HTTP, TCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPnPAlarm:
Alarm trigger: Alarm notification, motion detection
Alarm actions: Full time, event trigger recording, alert notificationsGeneral:
Housing: IP66 weather resistant
Rated voltage: 12 V DC, or IEEE 802.3af PoE
Power consumption: Typical: 2 W (IR LED turn on) / Max: 4 W
Dimension: 148 mm (diameter) x 122 mm (H)
Operating temperature: -10 ~ 60 °C
Operating humidity: 10 ~ 80% (non-condensing)This product is subject to the GPL v2.