

Item no.: 312101

NET-PWRCTRL HOME - 3 internet/ethernet outlets

from **103,66 EUR**

Item no.: 312101
shipping weight: 1.00 kg
Manufacturer: ANEL



Product Description

ANEL-Elektronik NET-PwrCtrl HOME

The brand new Power-Outlet controlled over Ethernet:

- 3 independent outlets controlled over Internet / Ethernet from the Internet browser or desktop. A web server in the device communicates with the network.
- Control from the Internet (World Wide)
- Wireless control over converter
- Automatic recognition on the network (DHCP)
- Automatic time setting from a NTP Server
- Call with hostname = eg: http://net-control or IP (hostname = device name)
- Free choice of the HTTP ports (80, multiple devices accessible from the Internet)
- 3x 4 timer + 3x random timer
- Automatic switching of sockets after restarting (power failure) selectable
- Sockets can be blocked
- No software (except web browser) is needed to control or set
- Controlled from an operating system (with a web browser)
- Additional Windows program to expand the functions (similar to USB-PwrCtrl) for the Ethernet and USB control
- Access control of user and administrator password (encrypted - SHA1)
- Report of the last 40 events
- DLL to integrate control of their own software
- Firmware upgrades via Ethernet at any time (Ethernet bootloader)
- No stand-by, no electricity consumption for the all connected devices
- Stable aluminium case, child protection in sockets, cable channel

Control

- Over network (Internet) from the browser: NET-PowerControl
- Software and network: NET-PwrCtrl Programm Screenshots
- DLL interface

Specifications

- Power supply: 230 V~ 50 Hz
- Cable length: 1,5 m
- Power consumption: 1,9 W
- Total power all outlets: 2300 W
- Dimensions: L 170 x B 120 x H 76 mm

System requirements

- Windows 98, ME, 2000, XP, VISTA, 7
- LAN

Delivery contents

- Power Line, software CD-ROM, main cable, Ethernet cable

LAN interface

- Standards compliance: IEEE 802.3 (10 Base-T)
- Data transfer rates: 10 MBit/s
- Protocols: ARP, IP, NetBIOS Name Service, ICMP (Ping), UDP, TCP, DHCP, HTTP, TP (RFC-868)
- Connector type: RJ-45
- Cable compatibility: 100 BASE-TX: Category 5, 2 4 UTP; 10 BASE-T: Category 3, 4, 5 2 UTP

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

