

Item no.: 312348 APAG05-2 - 2.4 GHz 2000 mW Outdoor Booster





Product Description

ALFA APAG05-2 - Wi-Fi Signal Outdoor Booster

The APAG05-2 Wi-Fi Signal Outdoor Booster is a highly efficient and compact unit designed to increase the performance and range of any 2.4 GHz wireless device. This includes Bluetooth, P2P, P2MP, 802.11b, 802.11b, 802.11b, 802.11b, and 802.11b+g access points and wireless routers.

The APAG05-2 extends the signal range, and in certain conditions, can double the range of these wireless devices. This eliminates the use of an additional radio with its associated data line, power outlet, signal interference, and setup headaches. The APAG05-2 is the fast and easy way to extend your signal range in any environment.

The APAG05-2 amplifies the signal of any 802.11b/g/n device for up to 2 Watt in power. That means your AP or wireless router can easily reach over 20~40 kilometers point to point with a high gain antenna in the open space. Features:

- High switching speed power gain controller
 High gain and low noise
 Powered through DC power injector
 Low power consumption
 Low heat generation
 Light woight

- Light weight

Applications:

- WLAN 802.11b, 802.11b+
- WLAN 802.11g
- WLAN 802.11n
 Bluetooth
- Digital Spread Spectrum on the ISM band

Absolute Maximum Ratings:

- Supply voltage: 15 V
 Rx input power: -10 dBm
 Tx input power: +23 dBm
 Operating temperature: -10°C ~ +50°C
 Storage temperature: -40°C ~ +90°C

- Model: APAG05-2
 Frequency band: 2.4 ~ 2.5 GHz
 Signal type: OFDM & DSSS
 TR switch time: < 1sec
 Rx. max. input power: -10 dBm
 Rx power gain: 23 dB max.
 Tx input power: 5 ~ 20 dBm
 DC supply voltage DC 12 V/1 A
 Tx linear output power: 2 W (at) 11b
 RF connector type: N female
 Operating temperature: -40°C ~ +40°C
 Storage temperature: -40°C ~ +90°C
 Connectors: N standard

Dimensions booster (incl. connectors and support)

- H: 3,7 cm
- L: 12 cm
 W: 14 cm

Dimensions injector (incl. connectors and support)

- H: 8 cm
 L: 4,5 cm
 W: 2,5 cm

Note: In accordance with the applicable requirements in Germany the radiated power (EIRP) of a wireless device should not exceed 20 dbm (100 mW). Please note the telecommunications law in your respective country.

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

