

Item no.: 316847

RFA-12-A95-CAX-A12 - 19" wall-mounted cabinet, 3 sections, 6 + 12 + 2 HU, 50 kg load capacity

from **539,73 EUR**

Item no.: 316847
shipping weight: 39.00 kg
Manufacturer: Triton



Product Description

Triton RFA-12-A95-CAX-A12 - 19" Wall-mounted cabinet, 3 sections, 6 + 12 + 2 HU, 50 kg load capacity [1st section](#)

The first section allows the installation of 19 equipment with a maximum height of 6 HU and a depth of 450 mm. The device is positioned vertically and 19 rails are infinitely adjustable over the full depth of the cabinet. On the back wall is a cable entry as well as on the top and bottom of the cabinet. Cable connections between sections allow the opening at the central divider. All cable entries have break-out covers. [2nd section](#)

The second section offers a mounting width of 19, height of 12 HU and depth of 450 mm. Mounting rails are infinitely adjustable within the whole depth. This section is usually used for structured cabling and active elements of the network. Here are individual services connected to the work places. The recommended capacity is up to 48 work places (2 ports per work place according to standards). [3rd section](#)

The third section occupies the whole bottom area of the wall cabinet. There is space for a device with a maximum depth of 800 mm, width of 19 and a height depending on the model of the cabinet from 2 to 7 HU. Access to this section is provided by a door on the right side of the cabinet. Sufficient space must be kept next to the cabinet for device installation and maintenance. [Flexible door opening](#)

The hinge system allows the door to be opened up to 180°. [Adjustable vertical rails](#)

One pair of vertical 19 rails is freely adjustable within the cabinet depth. This simplifies mounting devices and organizing connecting cables. [Rigid construction](#)

High-quality workmanship and up-to-date technologies ensure a perfect look of the cabinet. [Bottom section for servers](#)

19 section in the lower part of the cabinet is designed for installation of servers and other devices on sliding rails. It may have a capacity of 2 to 7 Units. Each section of the cabinet is closed by a lock, on request with a unique key. [Server installation](#)

Rack-mount servers or similar devices with a depth of up to 800 mm are mounted into the cabinet using special telescopic rails which are specific to each device and are not part of the cabinet. [Cooling of installed equipment](#)

Cooling by air flow through perforation of the frame and side door can be supported by installing fans for wall-mounted cabinets.

[Size in mm:](#)

- 700 x 540 x 900

[Max. server height for 3rd section:](#)

- 2 HU

[Material](#)

- Safety hardened glass 5 mm thick
- Steel sheet

[Supply includes](#)

- 4x keys - front door
- 6x screws 6x50
- 6x washers 6,6
- 6x dowels 10
- 8x captive nuts M6
- 1x blanking panel with brush

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

