

Item no.: ACRPSMA

ACRPSMA - flex-guide cable, low loss, 50 cm, RP-SMA

from **7,99 EUR**

Item no.: ACRPSMA
shipping weight: 0.10 kg
Manufacturer: MikroTik



Product Description

MikroTik ACRPSMA flex-guide cable, low loss, 50 cm, RP-SMA

A super low loss RPSMA cable for superior connection quality, suited for indoor and outdoor use, this cable provides superior matching and loss values. The name of this cable comes from combining the words flexible and waveguide to denote the high-end features of this product. The inner conductor is silver plated copper, and both connectors are soldered, not crimped, for the best possible signal quality. Ideally suited for the BaseBox and other products with RP-SMA connectors, and works with most antennas.

- Product code: ACRPSMA
- RPSMA: Soldered on both ends
- Inner conductor: Silver-plated copper
- Frequency: Up to 6 GHz
- Total signal loss at 6 GHz: 0.59 dB (with connectors)
- Matching: Better than -20 dB
- Suited for: Outdoor use
- Cable length: 500 mm (19.7)
- Outer diameter: 4.2 mm (0.2)
- Min. bending radius static: 8 mm (0.3)
- Min. bending radius repeated: 40 mm (1.6)
- Operating temperature: -55°C to 125°C

Fits: RB912UAG-5HPnD-OUT, Ubiquiti Rocket and others

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

