

Item no.: PRO-SECTOR35016HV

SEC3516DP - 3.5 GHz, 2x 16 dBi Sector Antenna + Box

from **80,28 EUR**

Item no.: PRO-SECTOR35016HV

shipping weight: 1.60 kg

Manufacturer: ITELITE



Product Description

IT ELITE PRO-SEC35016DP - 3.5 GHz, 2x 16 dBi Sector Antenna + Box

Professional sector antenna with space for electronics working in the 3.5 GHz band with 2x 16 dBi gain. The weatherproof outdoor enclosure with two independent sector antennas offers enough space for RouterBOARDS or any other electronic equipment.

The enclosure is equipped with a special RJ-45 waterproof Ethernet connector for an easy connection to network and PoE. Specifically designed for operation under severe weather conditions, since proper materials allow operation without the risk of corrosion even in saltwater environments. Professional mounting system with 0-15 degrees scale guarantees easy and smooth tilt adjustment, as well as rock-stable operation.

This product is for point-to-multipoint applications for highly professional solutions. Inside the enclosure are suitable posts for MikroTik RouterBOARDS of the 411 and 433 series.

Key Features:

- 2x 16 dBi sectorial gain
- Dual polarization H&V in one case
- Special outdoor weatherproof enclosure
- Suitable for Mikrotik RouterBOARDS
- Mounting for Ubiquiti Rocket
- Highest International Protection Rating IP 66
- High-quality construction
- Minimized sidelobe levels
- Vertical polarization
- Heavy-duty mounting elements
- Easy elevation and tilt adjustment
- Designed for all-weather operation

Applications:

- 3.5 GHz band Wireless LAN
- WiMAX
- MIMO standard
- Point-to-multipoint applications

Electrical Properties

- Frequency: 3.4 - 3.7 GHz
- Gain: 2x 16 dBi
- Polarization: Dual H&V
- Beamwidth deg horizontal: 90°
- Beamwidth deg vertical: 10°
- VSWR:
- Impedance: 50 Ohm
- Front to back ratio: >35 dB
- Lightning protection: DC ground

Enclosure Properties

- Technology: Microstrip
- Material: UV-resistant
- Color: White
- Ingress Protection Rating (EN 60529): IP 66
- Min. temperature: -40°C / -40°F
- Max. temperature: 80°C / 176°F

Mechanical Properties

- Compatible with: RB411 and RB433 series
- Input connector: SMA female, U.FL or MMCX pigtail optional
- Enclosure connector: Waterproof Ethernet connector
- Outside dimensions: 580 x 150 x 60 mm / 22.8 x 5.9 x 2.4"
- Weight: 2.1 kg / 4.7 lbs

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

