

Item no.: RB911G-5HPACD-NB

RB911G-5HPACD-NB - NetBox 5, 5 GHz 802.11ac 2x2 dual-chain wireless

from **92,18 EUR**

Item no.: RB911G-5HPACD-NB

shipping weight: 0.70 kg

Manufacturer: MikroTik



Product Description

MikroTik RB911G-5HPACD-NB, NetBox 5, built-in 5 GHz 802.11ac 2x2 dual-chain wireless, 2x RP-SMA

The NetBox is a dual-chain outdoor AP/CPE/Point-to-Point device with RP-SMA connectors for antennas, and a cable hood for protection against moisture. This device supports the new 802.11ac standard for increased wireless speed (866 Mbit data rate and 20/40/80 MHz channels).

The case can be opened with one hand and is protected against the elements. USB, Ethernet and grounding wire exits are provided on the bottom, behind a protective door. Comes with a mounting loop for tower/pole mounting, and a separate DIN rail mount is also provided. The package also includes a PoE injector and power supply unit.

- Frequency range: 5150 MHz - 5875 MHz
- CPU: QCA9557 720 MHz network processor
- Memory: 128 MB DDR onboard
- Ethernet: 1x Gigabit port with Auto-MDI/X
- Wireless: QCA9882 5 GHz 802.11ac, 2x RP-SMA connectors, dual-chain
- Connector type: RP-SMA female (outside thread)
- Extras: Beeper, signal and status LEDs, voltage and temperature sensors
- Expansion: USB 2.0 port
- Power options: PoE: 8-30 V DC on Ether1 (non 802.3af)
- Consumption: 12 W at 24 V
- Dimensions: 246 x 135 x 50 mm
- Weight: 390 g
- OS: MikroTik RouterOS, Level4 license
- Kit includes: RB912 outdoor unit, PoE injector, mounting loop, DIN rail mount, mounting ring

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

