

Item no.: SEC-CC-2-14

# SEC-CC-2-14 - Sector Carrier Class Antenna 2-14 2x2 H+V

91,<sup>52</sup> EUR

Item no.: SEC-CC-2-14 shipping weight: 3.60 kg Manufacturer: RF Elements



### Product Description

RF Elements Sector Carrier Class Antenna 2-14 2x2 H+V

Sector Antenna with Carrier Class Performance

CARRIER CLASS Sectors are addressing customer requirements for RF performance, co-location noise resistance, ease of installation and cost efficiency. The antennas feature the innovative BackShield(TM), a patent pending system of frequency selective reflectors incorporated into the antenna structure to attenuate side lobes and back side near-field

Sector Antenna 2.4 GHz 14 dBi is a dual polarization version of CARRIER CLASS Sector with one horizontal and one vertical polarization antenna. Specifications

Physical

- Antenna connection: 2x RP-SMA on integrated semi-flex pigtails

- Antenna type: 2.4 GHz, 14 dBi
   Enviromental: IP55
   Temperature: -26°C to +60°C (-15°F to +140°F)
   Wind Survival: 160 km/hour

- Weight: 3.9 kg
  Dimensions: Retail box: 97 x 22 x 10 cm

#### Performance

- Frequency range: 2400 2485 MHz
  Gain max.: 13.8 dBi
  Gain typical: 13.5 dBi
  Polarization: Dual linear H + V

- Azimuth beam width: -3 dB H 75° / V 69°
  Elevation beam width: -3 dB H 14.5° / V 14°
  Azimuth beam width: -6 dB H 108° / V 100°

- Elevation beam width: -6 dB H 20° / V 19°
  Front-to-back ratio (Min): 24 dB
  Cross pol isolation: H 15 dB / V 13.5 dB
- Impedance: 50 OhmVSWR max.: 1.8
- VSWR typical: 1.4
  Isolation between ports: 18 dB

## Compatible wireless platforms

- RF elements(R): StationBox(R) S, StationBox(R) S CARRIER CLASS, RockShield(TM)
   Cambium Networks(TM): ePMP(TM) 1000 Connectorized Radio\*
   MikroTik(TM): BaseBox\*\*, NetBox\*\*
   Ubiquiti Networks(TM): UBNT Rocket(TM) M2, UBNT Rocket(TM) M2 Titanium

\*with EasyBracket(TM) for ePMP(TM)\*\*with EasyBracket(TM) 912



# Scan this QR code to view the product

All details, up-to-date prices and availability

