

Item no.: RB912UAG-5HPND-OUT

## RB912UAG-5HPND-OUT - RouterBOARD, 600 MHz, 64 MB RAM, 5 GHz 802.11a/n, OUTDOOR

from **75,03 EUR**

Item no.: RB912UAG-5HPND-OUT  
shipping weight: 0.70 kg  
Manufacturer: MikroTik



### Product Description

MikroTik RouterBOARD RB912UAG-5HPND-OUT

The RB912 is also available in an outdoor enclosure, fitted with two RP-SMA connectors for antennas, and a cable hood for protection against moisture. Also available are three additional places for antenna connectors, in case you wish to use the RB912 miniPCIe slot for one more wireless interface to make it a dual band device.

The case can be opened by one hand and is protected against the elements. USB, Ethernet and a Grounding wire exits are provided on the bottom, behind a protective door. Comes with a mounting loop for tower/pole mounting, and a separate DIN rail mount is also provided. Package also includes a PoE injector and power supply unit.

- Features: 1x Ethernet, 1x miniPCIe, USB, additional memory, Gigabit, high-power, dual-chain, outdoor-case
- CPU: Atheros AR9342 600 MHz network processor
- Memory: 64 MB DDR2 onboard memory
- Ethernet: 1x Gigabit port with Auto-MDI/X
- Wireless: Built-in 5 GHz AR9283 802.11a/n, 2x RP-SMA connectors
- Extras: Reset, beeper, signal and status LEDs, SIM slot (requires 3g miniPCIe card)
- Expansion: miniPCIe slot for 802.11 or 3G (using 3G disables the USB port), USB 2.0 port
- Power options: PoE: 8-30V DC on Ether1 (non 802.3af).
- Dimensions: 246 x 135 x 50 mm
- Weight: 390g
- Max. consumption: 14 W at 24 V
- OS: MikroTik RouterOS, Level4 license (supports wireless AP mode)
- Kit includes: RB912 outdoor unit, PSU, PoE injector, mounting loop, DIN rail mount
- TX/RX at MCS0: 30 dBm / -96 dBm
- TX/RX at MCS7: 24 dBm / -78 dBm
- TX/RX at 6 Mbit: 30 dBm / -96 dBm
- TX/RX at 54 Mbit: 27 dBm / -80 dBm
- Frequency range: 4900-5920 MHz

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

