

Item no.: RBMAP2ND

RBMAP2ND - mAP with 650 MHz CPU, 64 MB RAM, 2x LAN

from **40,72 EUR**

Item no.: RBMAP2ND shipping weight: 0.30 kg Manufacturer: MikroTik



Product Description

RBMAP2ND - mAP with 650 MHz CPU, 64 MB RAM, 2x LANThe mAP is a tiny size wireless Access Point with full RouterOS capabilities. It is very portable, since it accepts power from a wide variety of sources - USB, PoE and power jack. In addition to using this device as a small and portable AP, it also works as a PoE injector - the second Ethernet port provides up to 500 mA of power to another device, for example, you can connect a SXT CPE device to it.

- PoE in 10-57 V
- Built in 2.4 GHz AP
- Built iff 2.4 GHZ AP
 microUSB for a 3G/4G modem, or for power input
 Station or AP mode wireless
- Passive PoE output (same as input voltage)

Specifications

- Product code: RouterBOARD mAP2nD
 CPU: Qualcomm Atheros AR9531 650 MHz

- RAM: 64 MB DDR2:
 Ethernet: 2x 10/100 Mbit/s Ethernet with Auto-MDI/X
 Storage: 16 MB built in flash storage
 Wireless: QCA9531, 2.4 GHz 802.11b/g/n built in
- Antenna: 1.2 dBi built in
- Power input: Passive PoE 10-57 V and 802.3af/at, supports powering from USB
- Power output: Passive PoE output, up to 500 mA on Ether 2
 Case dimensions: 68 x 68 x 19 mm

- Temperature: -10°C to +70°C tested
 OS: MikroTik RouterOS v6, Level 4 license
 Included: mAP device, 24 V/0.8 A power adapter, microUSB type B to USB type A adapter

Specifications



