

Item no.: 312767

RUA-09-AS5-CAX-A1 - Wall-mounted 19" cabinet, 9 HU, 495 mm depth

from **233,87 EUR**

Item no.: 312767
shipping weight: 14.30 kg
Manufacturer: Triton



Product Description

TRITON RUA-09-AS5-CAX-A1 - Wall-mounted 19" cabinet, 9 HU, 495 mm depth

RUA wall-mounted cabinet is one of the one-sectioned wall-mounted cabinets. Thanks to removable side panels, installed devices are very easily accessible. Cabinet has a robust welded construction. High quality processing and the up-to-date technology ensure a perfect look of the cabinet and maximal loading capacity of 30 kg. Cabinet door is glass standardly but it can be steel or perforated as required. The hinge system enables almost 180° wide opening of the door. Doors can be easily removed.

REMOVABLE SIDE PANELS:

Removable side plates enable access to the installed devices from the rear side without demounting.

Blanking panels for installation of cooling ventilators:

RUA has now in all its versions six break-out blanking panels for installation of cooling ventilators RAB-CH-X30-X1 (three are in the upper and three in the lower part of a cabinet). RUA cabinet enables installation of devices that could not be cooled sufficiently in wall-mounted cabinets in the past and therefore had to be installed into free-standing cabinets only.

ADJUSTABLE VERTICAL RAILS:

One pair of vertical 19 rails is freely adjustable in any depth of the cabinet. This simplifies mounting of the device and organisation of connecting cables.

BREAKOUT-TYPE BLANKING PANELS:

Cable openings covered with breakout-type blanking panels are ready in the top, bottom and rear part of the cabinet. Use a plastic frame and a blanking panel with a brush, that are parts of the cabinet supply, to seal the cabinet opening against dust penetration.

Size in mm:

- 500 x 395 x 495

Description. Usage

- 19 one-sectioned wall-mounted cabinet with IP 30 protection
- Removable side panels are locked with locks
- Cabinet is to be hanged right on the wall
- Cabinet components include two sliding vertical rails
- Cabinet construction:
 - welded frame with removable side panels secured by locks
 - glass door: safety hardened glass, thickness 5 mm
- Cabinets are intended for installation of data and telecommunication devices and their distribution systems
- The frame of the cabinet and all the removable parts are connected with earthing cables that have to be properly fixed and inserted into connectors during all the time when using the cabinet
- There is one M8 screw placed on the bottom part of the cabinet as an earthing main point
- Cable openings covered with breakout-type blanking panels are placed in the top and the bottom part of the cabinet rear side, others are in the top and the bottom side of cabinet

Supply includes:

- Key - front door 2x
- Screw 6x50 4x
- Washer 6,6 4x
- Dowel 10 4x
- Captive nut M6 8x
- Blanking panel with brush 1x

Material:

- Safety hardened glass 5 mm thick
- Steel sheet

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

