

from 287,06 EUR

Item no.: 312825 shipping weight: 37.40 kg Manufacturer: Triton

Item no.: 312825 RBA-15-AD5-CAX-A1 - Wall-mounted 19" cabinet, 2-sectioned, 15 HU, 515 mm depth



Product Description

TRITON RBA-15-AD5-CAX-A1 - Wall-mounted 19" cabinet, 2-sectioned, 15 HU, 515 mm depth

The data and telecommunicationcabinet is a very successful version of two-sectioned cabinets. The parts to be opened of the cabinet enable an easy access to the rear cabinet section.

The cabinet has a robust welded construction. High-quality processing andup-to-date technologies ensure a perfect look of the cabinet.

The cabinetdoor is glass by default but can be steel or perforated if required. The hinge system enables an almost 180° wide opening of the door. The doorcan be easily removed and mounted for changing the door openingdirection.

EASY ACCESS:

The parts to be opened of the cabinet enable an easy access to the rear cabinetsection. You can easily remove the front part of the cabinet afterunlocking chain shackles. All parts are interconnected and grounded.

ADJUSTABLE VERTICAL RAILS:

One pair of vertical 19 rails is freely adjustable in any depth of thecabinet. This simplifies mounting the devices and organizing connecting cables.

BREAKOUT-TYPE BLANKING PANELS:

Cable openings covered with breakout-type blanking panels are ready in the top, bottom and rear part of the cabinet. Use a plastic frame and ablanking panel with a brush that are part of the cabinet supply toseal the cabinet opening against dust. Size in mm:

• 770 x 600 x 515

Description, usage

- 19 two-sectioned wall-mounted cabinet with IP 30 protection
- Cabinet to be hanged on a wall
 Cabinet components include two sliding vertical rails
- Cabinet construction:
 Compact welded cabinet
 - Glass door: safety hardened glass, thickness 5 mm
- Cabinets are intended for installing data and telecommunication devices and their distribution systems
 The frame of the cabinet and all the removable parts areconnected with grounding cables that have to be properly fixed andinserted into connectors during all the time when using the cabinet
- •
- There is one M8 screw placed on the bottom part of the cabinet as a main grounding point Cable openings covered with breakout-type blanking panels areplaced in the top and the bottom part of the cabinet's rear side, othersare in the top and the bottom side of the cabinet

Supply includes:

- Key front door 2x
 Screw 6x50 4x
 Washer 6,6 4x
 Dowel 10 4x
 Captive nut M6 8x
 Blanking panel with brush 1x

Material:

- Safety hardened glass 5 mm thickSteel sheet

Specifications



10