

Item no.: 312829

## RBA-09-AD6-CAX-A1 - Wall-mounted 19" cabinet, 2-sectioned, 9 HU, 615 mm depth

from **250,86 EUR**

Item no.: 312829  
shipping weight: 23.00 kg  
Manufacturer: Triton



### Product Description

TRITON RBA-09-AD6-CAX-A1 - Wall-mounted 19" cabinet, 2-sectioned, 9 HU, 615 mm depth

The data and telecommunication cabinet is a very successful version of two-sectioned cabinets. The parts of the cabinet which can be opened enable an easy access to the rear cabinet section.

The cabinet has a robust welded construction. High quality processing and up-to-date technologies ensure a perfect look of the cabinet.

The cabinet door is glass by default but can be steel or perforated if required.

The hinge system enables an almost 180° wide opening of the door. The door can be easily removed and mounted for changing the door's opening direction.

#### EASY ACCESS:

The parts of the cabinet that can be opened enable an easy access to the rear cabinet section. You can easily remove the front part of the cabinet after unlocking chain shackles. All parts are interconnected and grounded.

#### ADJUSTABLE VERTICAL RAILS:

One pair of vertical 19 rails is freely adjustable in any depth of the cabinet. This simplifies mounting devices and organizing connecting cables.

#### BREAKOUT-TYPE BLANKING PANELS:

Cable openings covered with breakout-type blanking panels are ready in the top, bottom and rear part of the cabinet. Use a plastic frame and a blanking panel with a brush that are part of the cabinet supply to seal the cabinet opening against dust.

#### Size in mm:

- 500 x 600 x 615

#### Description, usage

- 19 two-sectioned wall-mounted cabinet with IP 30 protection
- Cabinet to be hanged on a wall
- Cabinet components include two sliding vertical rails
- Cabinet construction:
  - Compact welded cabinet
  - Glass door: safety hardened glass, thickness 5 mm
- Cabinets are intended for installing data and telecommunication devices and their distribution systems
- The frame of the cabinet and all the removable parts are connected with grounding cables that have to be properly fixed and inserted into connectors during all the time when using the cabinet
- There is one M8 screw placed on the bottom part of the cabinet as a main grounding point.
- Cable openings covered with breakout-type blanking panels are placed in the top and the bottom part of the cabinet's rear side, others are in the top and the bottom side of the cabinet

#### Supply includes:

- Key - front door 2x
- Screw 6x50 4x
- Washer 6,6 4x
- Dowel 10 4x
- Captive nut M6 8x
- Blanking panel with brush 1x

#### Material:

- Safety hardened glass 5 mm thick
- Steel sheet

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

