

Item no.: SXTSQ-5-AC

RBSXTSQG-5ACD - SXTsq 5 ac - with 16 dBi 5 GHz antenna, dual-chain 802.11ac wireless

from **55,79 EUR**

Item no.: SXTSQ-5-AC
shipping weight: 0.50 kg
Manufacturer: MikroTik



Product Description

MikroTik SXTsq 5 ac - RBSXTsqG-5acD with 16 dBi 5 GHz antenna, dual-chain 802.11ac wireless

The SXTsq 5 ac is a compact and lightweight outdoor 5 Ghz 802.11ac wireless device with an integrated antenna, perfect for point-to-point links or as a CPE unit. The device includes one 10/100/1000 Mbit Ethernet port to fully utilize speeds that 802.11ac protocol provides.

The SXTsq 5 ac retains a 16 dBi antenna like the SXT 5 ac, MikroTik's previous model, yet the antenna design has been improved and the physical size has been dramatically reduced - the SXTsq is two times thinner.

The weatherproof enclosure includes slots for directly attaching a hose clamp mount in three different mounting places, with the ability to be mounted on horizontal railings. There is also an easily accessible grounding connection to protect it against lightning. Included:

- 24 V, 0.38 A power adapter
- Metal ring
- Gigabit PoE injector

- Product code: RBSXTsqG-5acD
- CPU: IPQ-4018, 4 cores, nominal frequency 716 MHz
- Size of RAM: 256 MB
- Storage: 16 MB Flash
- 10/100/1000 Ethernet ports: 1
- Wireless bands: 5 GHz radio
- Wireless regulations: Specific frequency range may be limited by country regulations
- Operating frequency: 5150 - 5875 MHz
- Protocols: 802.11a/n/ac
- Chains: 2
- Antenna gain: 16 dBi
- Antenna beam width: 23°
- Wireless chip model: IPQ-4018
- PoE in: Yes
- Supported input voltage: 10 - 30 V, passive PoE
- Ingress protection: IP55
- Dimensions: 129 x 129 x 34 mm; package: 255 x 180 x 45 mm
- Weight: Unit: 295 g; package: 492 g
- Operating temperature: -40°C to 70°C
- License level: 3
- Operating system: RouterOS
- Max. power consumption: 7 W

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



