

Item no.: CRS328-24P-4S+RM

CRS328-24P-4S+RM - Cloud Router Switch, 800 MHz CPU, 512 MB RAM, 24 Ports

from **475,87 EUR**

Item no.: CRS328-24P-4S+RM
shipping weight: 4.30 kg
Manufacturer: MikroTik



Product Description

MikroTik Cloud Router Switch 328-24P-4S+RM with 800 MHz CPU, 512 MB RAM, 24x LAN

CRS328-24P-4S+RM is a 28 independent port switch. It has 24 Gigabit Ethernet ports, which offer different power output options: Passive PoE, low voltage PoE, 802.3af/at (type 1 PoE/type 2 PoE+) with auto-sensing. The four SFP+ ports provide up to 10 Gbps connectivity options either via optical fiber or Ethernet modules (not included).

CRS328-24P-4S+RM comes in a 1U rackmount case with 100-240 V AC 500 W power supply built-in. The device consumes up to 44 W leaving guaranteed 450 W (3x 150 W per every 8 Ethernet ports) to power your PoE devices. Each port can provide up to 30 W with high voltage, and 26 W with low voltage power output.

The device has a dual boot feature that allows you to choose between two operating systems - RouterOS or SwOS. If you prefer to have a simplified operating system with switch-specific features only, use SwOS. If you would like the ability to use routing and other Layer-3 features in your CRS, use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings. All the feature set comes at a disruptive price, providing best price/performance on the market.

- Product code: CRS328-24P-4S+RM
- CPU: ARM v7 800 MHz
- RAM: 512 MB
- Storage type: Flash
- Storage size: 16 MB
- Switch chip model: 98DX3236A1
- 10/100/1000 Ethernet ports: 24
- SFP+ cages: 4
- Operating system: SwOS / RouterOS (dual boot)
- Supported input voltage: 100 - 240 V
- Dimensions: 443 x 305 x 44 mm
- Operating temperature: -20°C to +60°C tested
- Max. power consumption: 44 W
- Serial port: RJ45
- License level: 5

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

