

Item no.: RB912UAG-6HPND-OUT RB912UAG-6HPND-OUT - 6 GHz outdoor wireless device





Product Description

MikroTik RB912UAG-6HPnD-OUT - 6 GHz outdoor wireless device

- Attention: This product is available for 5.9 - 6.4 GHz license holders only, it is NOT for unlicensed ISM bands! In order to be able to order BaseBox 6, a presentation of the respective license (document) is necessary. -

The BaseBox 6 in an outdoor wireless device, based on our popular RB912 model, fitted with two SMA connectors for antennas, and a cable hood for protection against moisture. Also available are three additional places for antenna connectors, in case you wish to use the BaseBox miniPCle slot for one more wireless interface to make a dual-band device, or a 3G/4G modem. The case can be opened with one hand and is protected against the elements. USB, Ethernet and a grounding wire exit are provided on the bottom, behind a protective door.

The BaseBox 6 model operates in the 6 GHz wireless spectrum, in regions where this range is available. It comes with a mounting loop for tower/pole mounting, and a separate DIN rail mount is also provided. Package also includes a PoE injector and power supply unit.

- Product code: RB912UAG-6HPnD-OUT
- CPU: AR9342
- CPU nominal frequency: 600 MHz Size of RAM: 64 MB •
- ٠
- Storage: Flash 64 KB, NAND 128 MB
 10/100/1000 Ethernet ports: 1
 Wireless: 6 GHz 802.11a/n, dual-chain

- Wireless chip: AR9342
 Antenna headers: 2x RP-SMA connectors
- PoE in: Yes
- Supported input voltage: 10 30 V
 USB: 1x USB 3.0 type A, max. 1 A
- PCB temperature monitor: Yes
- Voltage monitor: Yes .
- •
- Beeper: Yes SIM slot: Yes, Mini SIM Dimensions: 246 x 135 x 50 mm
- Operating temperature -40°C to +70°C tested
 Max. power consumption: 23 W
- License level: 4
- •
- Operating system: RouterOS

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

