

Item no.: CRS305-1G-4S+IN

CRS305-1G-4S+IN - Cloud Router Switch 305-1G-4S+IN with 800 MHz CPU

from **126,45 EUR**

Item no.: CRS305-1G-4S+IN
shipping weight: 0.50 kg
Manufacturer: MikroTik



Product Description

MikroTik CRS305-1G-4S+IN - Cloud Router Switch 305-1G-4S+IN with 800 MHz CPU

The CRS305 is a compact yet very powerful switch, featuring four SFP+ ports for up to 10 Gbit per port. The device has a 1 Gbit copper Ethernet port for management access and two DC jacks for power redundancy. The device has a very sleek and compact metallic case without any fans for silent operation.

The device has a dual boot feature that allows you to choose between two operating systems - RouterOS or SwOS. If you prefer to have a simplified operating system with only switch specific features, use SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings. All the feature set comes with a disruptive price, providing the best price/performance on the market.

Specifications

- 4x SFP+ ports
 - 1 Gigabit Ethernet ports
 - Non-blocking throughput: 41 Gbps
 - Switching capacity: 82 Gbps
 - Forwarding rate: 61 Mpps
 - 2x DC jack for redundancy
 - Maximum power consumption: 12 W (with attachments 18 W)
 - Supports PoE+ IEEE 802.3at/af and passive PoE 12-57 V
 - Metal enclosure
 - Fanless
-
- Product code: CRS305-1G-4S+IN
 - CPU: 98DX3236A1 800 MHz
 - RAM: 512 MB
 - Storage type: Flash
 - Storage size: 16 MB
 - Switch chip model: 98DX3236A1
 - 10/100/1000 Ethernet ports: 1
 - SFP+ cages: 4
 - Operating system: SwOS/RouterOS (dual boot)
 - PoE in: Yes
 - Supported input voltage: 12 - 57 V (DC jack and PoE in)
 - Number of DC jacks: 2
 - Dimensions: 141 x 115 x 28 mm
 - Operating temperature: -40°C to +70°C tested
 - Max. power consumption: 12 W
 - License level: 5

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



