

Item no.: TPA-SMA

TPA-SMA - TwistPort(TM) Adaptor with SMA Connectors

from **19,12 EUR**

Item no.: TPA-SMA
shipping weight: 0.30 kg
Manufacturer: RF Elements



Product Description

RF Elements TPA-SMA - TwistPort(TM) Adaptor with SMA Connectors

The TwistPort(TM) Adaptor with SMA connectors is designed to provide two RP-SMA male coaxial interfaces (dual linear H+V) and can be connected to TwistPort(TM) enabled antennas.

Technical Data

- Antenna connection: TwistPort(TM) - Quick locking waveguide port
- Radio connection: 2x RP-SMA male
- Materials: Insert - aluminium alloy, adaptor - UV stabilized and weather resistant ABS plastic
- Flame rating: UL 94 HB
- Temperature: -40°C to +60°C (-40°F to +140°F)
- Wind survival: 160 km/h
- Weight: 0.28 kg
- Dimensions: 15.5 x 10.0 x 9.7 cm

Performance

- Frequency range: 5180 - 6400 MHz
- Polarization: Dual linear H + V
- VSWR max.: 1.8
- Impedance: 50 Ohm

Compatible Wireless Platforms

- RF elements(R): Any TwistPort(TM) Antenna

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

