

## Item no.: TPA-SMA **TPA-SMA - TwistPort(TM) Adaptor with SMA Connectors**





## Product Description

RF Elements TPA-SMA - TwistPort(TM) Adaptor with SMA Connectors

The TwistPort(TM) Adaptor with SMA connectors is designed to provide two RP-SMA male coaxial interfaces (dual linear H+V) and can be connected to TwistPort(TM) enabled antennas.

Technical Data

- Antenna connection: TwistPort(TM) Quick locking waveguide port
   Radio connection: 2x RP-SMA male
   Materials: Insert aluminium alloy, adaptor UV stabilized and weather resistant ABS plastic
- Materials: insert autimitum anoy, adaptor 0v
  Flame rating: UL 94 HB
  Temperature: -40°C to +60°C (-40°F to +140°F)
  Wind survival: 160 km/h
  Weight: 0.28 kg
  Dimensions: 15.5 x 10.0 x 9.7 cm

Performance

- Frequency range: 5180 6400 MHz
  Polarization: Dual linear H + V
  VSWR max.: 1.8
  Impedance: 50 Ohm

Compatible Wireless Platforms

• RF elements(R): Any TwistPort(TM) Antenna



Scan this QR code to view the product All details, up-to-date prices and availability

