

Item no.: 323730

## BEACON I6 - Sticker Beacon, BT 4.0, iBeacon

from **6,68 EUR**

Item no.: 323730

shipping weight: 0.10 kg

Manufacturer: MINEW Technologies



### Product Description

Beacon i6 - Sticker Beacon, BT 4.0, iBeaconThe i6 is an ultra-thin iBeacon with ARM core chipset nRF51822 a BLE 4.0 technology. The device runs with the standard MiniBeacon firmware.

#### Features

- Programmed MiniBeacon standard firmware
- Ultra-thin, only 3.3 mm
- Max. 50 meters transmission distance
- Small size, user-friendly and portable
- Compatibility: Supports iOS 7.0+, Android 4.3+, Apple iBeacon(TM) standard, Bluetooth 4.0 (BLE) devices
- Battery Lifetime: 6 months, real-time battery level notification
- OTA and J-Link: Supports OTA, reserved J-Link port on the board for programming
- Configurable Parameters: UUID, major, minor, device name, password etc., special configuration app
- Transmission Power Levels: 8 adjustable levels, range from 0 to 7
- Transmission Power Range: -30 dBm to +4 dBm
- Soft Reboot: Reboot the device via command without any tools
- Connection Mode: Advertising mode, non connectable, configuration mode, connectable
- Mounting: 3 m brand adhesive for direct mounting to wall
- Shape: Ultra-thin 3.3 mm, battery replaceable design
- Case Color: White, can be customized
- Battery Model: 1x CR2016 coin battery, 3 V (not included)
- Operation Voltage: 1.8 - 3.6 V
- Transmission Circuit: 10.5 mA (max.)
- Transmission Range: Max. 50 meters
- Antenna: 50 ohm, on board, PCB antenna
- Accessories: Double-sided adhesive tape
- Weight: 4 g, with battery
- Size: 32 x 23 x 3.3 mm

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

